



Reference: 10284784
EAN 13: 3427580837258

CONTACT

Markets and Products Information
rollingstock.business@lynxéogroup.com

SHIELDED HIGH TEMPERATURE EXTRA-FLEXIBLE POWER CABLES

FLAMEX® EN 50382-2 FFXS shielded power cables are designed with extra flexible conductors as per jumper cables. They are used for installations where enhanced electrical screening (EMC) is required. Able to withstand higher operating temperatures, these silicone-based cables allow to save cable weight.

STANDARDS

Product EN 45545-2 (HL3); EN 50382-2; IEC 60228

DESIGN

1. Conductor

Extra flexible class 6 copper according to IEC 60228
- tinned copper for 120°C Class
- plain copper for 150°C Class

2. Insulation

Cross-linked silicone type EI 111 according to EN 50382-1
Separator: Unweaved tape

3. Screen

Tinned copper wire braid
Separator: Unweaved tape

4. Outer sheath

Cross-linked silicone type EM 107 according to EN 50382-1
Colour: black outer layer

Examples of marking:

FLAMEX SI - EN 50382-2 - Voltage rate (1800V or 3600V) - cross-section mm² - FFXS - temperature class (120°C or 150°C) - Manufacturing n° - NEXANS 279 - week/year
DTREN 150068 - EN 50382-2 - 1800V - cross-section mm² - FFXS - temperature class (120°C) - Manufacturing n° - NEXANS 279 - week/year



Conductor flexibility
Extra-flexible
class 6



Halogen free
EN 60754-1 & EN
60684-2



Rated Voltage U_o/U_i
(Um)
1.8 / 3 (3.6) kV



Flame retardant
EN 60332-1-2



Fire retardant
EN IEC 60332-3-24
(cat C); EN IEC
60332-3-25
(EN50305)



Smoke density
EN/IEC 61034-2



Gases toxicity
EN 50305-9.2



Operating temp.
-50 ... 120 °C

CHARACTERISTICS**Construction characteristics**

Conductor material	Tin plated copper
Conductor flexibility	Extra-flexible class 6
Insulation	High temperature silicone
Screen	Tinned copper braid
Outer sheath	High temperature silicone
Halogen free	EN 60754-1 & EN 60684-2

Dimensional characteristics

Conductor cross-section	50 mm ²
Conductor diameter	9.5 mm
Braid section	7.5 mm ²
Nominal outer diameter	17.3 mm
Minimum outer diameter	16.6 mm
Maximum outer diameter	18.6 mm
Approximate weight	651 kg/km

Electrical characteristics

Rated Voltage U _o /U (U _m)	1.8 / 3 (3.6) kV
---	------------------

Usage characteristics

Flame retardant	EN 60332-1-2
Fire retardant	EN IEC 60332-3-24 (cat C); EN IEC 60332-3-25 (EN50305)
Smoke density	EN/IEC 61034-2
Gases toxicity	EN 50305-9.2
Operating temperature, range	-50 ... 120 °C
Electro magnetic interference resistance	Yes
Max. conductor temperature in service	120 °C
Overload maximum core temperature	140 °C
Chemical resistance	Good