



Reference: 10554181
Country Ref.: 13-MYS24P02R-V1
EAN 13: 8054803101480

CONTACT

Market information
 industryprojects.business@lynxeogroup.com

Digital feedback cables according to SIEMENS DRIVE CLIQ standard

STANDARDS

Product UL and CSA approval

DESIGN

Element 2x2x0.22 mm²

Conductor
 Bare copper stranded
Insulation
 Foam-skin PE

Colour code
 (Blu + Pink)+(Yellow + Green)

Element 2x2x0.15 mm²

Conductor
 Bare stranded copper

Insulation
 Foam-skin PE

Colour code
 (Blu + Pink)+(Yellow + Green)

Element 1x2x0.38 mm²

Conductor
 Tinned stranded copper

Insulation

Polyolefin
Colour code
 (Red + Black)

CHARACTERISTICS

Construction characteristics

Construction type	(2x2x0.22)C
Conductor material	Bare copper
Insulation	Polyolefin
Insulation colour	See Tab
Lay Up	Please request detailed data sheet



Operating temp.
 -20 ... 80 °C



Storage temperature, range
 -50 ... 80 °C



Oil resistance
 EN 50363-10-2



Flame retardant
 IEC/EN 60332-1-2; FT1; UL 1581 FT1

Construction characteristics

Shielding	≥85% tinned copper braid coverage
Taping	Non woven tape
Outer sheath	PVC
Sheath colour	Green RAL 6018

Dimensional characteristics

Nominal outer diameter	6.85 mm
Copper content	25 kg/km
Approximate weight	57 kg/km

Electrical characteristics

Rated Voltage Uo/U	30 V
Test voltage	500 V

Mechanical characteristics

Maximum acceleration	- m/s ²
Bending cycles	- Mio.
Speed	-

Usage characteristics

Field of application	Fixed installations
Minimum dynamic operating bending radius	7.5 (xD)
Operating temperature, range	-20 ... 80 °C
Storage temperature, range	-50 ... 80 °C
Oil resistance	EN 50363-10-2
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1



Operating temp.
-20 ... 80 °C



Storage temperature, range
-50 ... 80 °C



Oil resistance
EN 50363-10-2



Flame retardant
IEC/EN 60332-1-2; FT1; UL 1581 FT1