



**Reference:** 10554301  
**Country Ref.:** 13-MYE26Z09P-V1  
**EAN 13:** 8054803099084

#### CONTACT

Market information  
 industryprojects.business@lynxgroup.com

Measuring systems cables according to Lenze standard for dynamic applications, PUR jacket, resistant to oils, flame retardant, halogen-free

#### STANDARDS

**Product** UL and CSA approval

#### Design

**Pair 0.14 mmq**

Voltage Rate U=300V (UL/CSA)

Conductor: Bare copper

Insulation: Polyethylene

Twisted pairs colour: Black + Yellow; Black + Green; Black + Red

Taping: Non hygroscopic tape

Shield: Tinned copper braid cov. 75%

Overall Tape: Non hygroscopic tape

**Triad 0.14 mmq**

Voltage rate U=300V (UL/CSA)

Conductor: Bare copper

Insulation: Polyethylene

Twisted pair colour; Pink, Black, Grey

Taping: Non hygroscopic tape

Shield: Tinned copper braid cov. 75%

Overall tape: Non hygroscopic tape



Halogen free  
 Yes



Operating temp.  
 -20 ... 80 °C



Storage temperature, range  
 -50 ... 80 °C



Flame retardant  
 IEC/EN 60332-1-2; FT1; UL 1581 FT1



Oil resistance  
 EN 50363-10-2

**CHARACTERISTICS****Construction characteristics**

Construction type	3x(2x0.14)C+(3x0.14)C
Conductor material	Bare copper
Insulation	Polyolefin
Insulation colour	See Tab
Individual screen	Tinned copper braid
Lay Up	Please request detailed data sheet
Taping	Non woven tape
Outer sheath	PUR
Sheath colour	Green RAL 6018
Halogen free	Yes

**Dimensional characteristics**

Nominal outer diameter	9.2 mm
Approximate weight	96 kg/km
Copper content	37 kg/km

**Electrical characteristics**

Rated Voltage U <sub>0</sub> /U	300 V
Test voltage	1500 V

**Mechanical characteristics**

Speed	180 m/min
Maximum acceleration	10 m/s <sup>2</sup>
Bending cycles	5 Mio.

**Usage characteristics**

Field of application	Dynamic
Minimum dynamic operating bending radius	15 (xD)
Operating temperature, range	-20 ... 80 °C
Storage temperature, range	-50 ... 80 °C
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1
Oil resistance	EN 50363-10-2