



Reference: 10554367
 Country Ref.: 13-MYF17Z12P-V1
 EAN 13: 8054803097769

CONTACT

Market information
 industryprojects.business@lynxgroup.com

encoder cables with Polyolefin insulation and PUR Jacket UL-CSA approved

STANDARDS

Product UL and CSA approval

DESIGN

Insulation colour code:

1x2x0.18 mmq:

Brown + White

5x0.5 mmq:

Blue + Pink + Green + Yellow + Grey

2x2x0.18 mmq :

(Brown + White) + (Violet + Black)

5x0.5 mmq:

Blue + Pink + Green + Yellow + Grey

4x2x0.22 mmq:

(Brown + Black) + (Brown/Red)

(Yellow + Black) + (Yellow/Red)

(Green/Black) + (Green/Red)

(Grey/Black) + (Grey/Red)

2x0.5 mmq:

Brown + Yellow

3x2x0.18 mmq:

(Red + White) + (Red + Black)

(Black + White)

6x0.5 mmq:

3 x Red num. 4-6 + 3 x Black num. 1-3

5x2x0.18 mmq:

(Black + Orange) + (Black + Grey)


(White + Yellow) + (White + Grey) + (White + Brown)



无卤
是



存储温度范围
-50 ... 80 ° C



操作温度
-20 ... 80 ° C



耐油
EN 50363-10-2



阻燃 - 火焰
IEC/EN 60332-1-2; FT1; UL 1581 FT1

CHARACTERISTICS

结构特性

结构类型	(3x2x0.18+6x1)C
导体材料	镀锡铜线
绝缘	聚烯烃
绝缘色	See Tab
绞合	Please request detailed data sheet
Taping	Non woven tape
屏蔽	80% tinned copper braid coverage
外护套	PUR
护套颜色	Green RAL 6018
无卤	是

尺寸特性

标称外径	8.7 mm
铜含量	88 kg/km
近似重量	129 kg/km

电气特性

Rated Voltage U ₀ /U	300 V
测试电压	1500 V

机械特性

速度	220 m/min
Maximum acceleration	12 m/s ²
弯曲循环	10 Mio.

使用特性

应用类型	动态
最小弯曲半径 - 动态	10 (xD)
存储温度范围	-50 ... 80 °C
操作温度范围	-20 ... 80 °C
耐油	EN 50363-10-2
阻燃 - 火焰	IEC/EN 60332-1-2; FT1; UL 1581 FT1



无卤
是



存储温度范围
-50 ... 80 °C



操作温度
-20 ... 80 °C



耐油
EN 50363-10-2



阻燃 - 火焰
IEC/EN 60332-1-2; FT1; UL 1581 FT1