



Reference: 10554384
Country Ref.: 13-MYI17Z10P
EAN 13: 8054803097424

CONTACT

Market information
 industryprojects.business@lynxgroup.com

Measuring systems cables according to BOSCH REXROTH standard for extremely dynamic applications, PUR jacket, shielded, resistant to oils, flame retardant, halogen-free

STANDARDS

Product UL and CSA approval

Normative Reference

UL Recognized / CSA
 AWM 80°C - 300V
 AWM 75°C - 300V FT1

Oil Resistance:

IEC 50363-10-2

Flame Retardant

IEC 60332-1-2

FT1

UL 1581

EN 50265-2-1

Toxicity:

Halogen free

CHARACTERISTICS

Construction characteristics

Construction type	(4x2x0.25+2x1)C
Conductor material	Stranded tinned copper
Insulation	Polyolefin
Insulation colour	See Tab
Lay Up	Please request detailed data sheet
Taping	Soft tape
Shielding	≥85% tinned copper braid coverage
Outer sheath	PUR
Sheath colour	Orange RAL 2003
Halogen free	Yes



Halogen free
Yes



Operating temp.
-30 ... 80 °C



Storage temperature, range
-40 ... 80 °C



Oil resistance
EN 50363-10-2



Flame retardant
IEC/EN 60332-1-2; FT1; UL 1581 FT1

Dimensional characteristics

Nominal outer diameter	8.8 mm
Copper content	74 kg/km
Approximate weight	- kg/km

Electrical characteristics

Rated Voltage U _o /U	300 V
Test voltage	1500 V

Mechanical characteristics

Maximum acceleration	20 m/s ²
Bending cycles	5 Mio.
Speed	240 m/min

Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	7.5 (xD)
Operating temperature, range	-30 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Oil resistance	EN 50363-10-2
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1



Halogen free
Yes



Operating temp.
-30 ... 80 °C



Storage temperature, range
-40 ... 80 °C



Oil resistance
EN 50363-10-2



Flame retardant
IEC/EN 60332-1-2; FT1; UL 1581 FT1