



**Reference:** 10554638  
**Country Ref.:** B1100046409  
**EAN 13:** 8054803092344

### CONTACT

Market information  
 industryprojects.business@lynxéogroup.com

UL-listed control cables for fixed installation outside and inside cable tray and wind turbines, PVC jacket, unshielded, oil resistant, flame retardant, TC-ER and MTW approved, UL Listed

### STANDARDS

**Product** UL 1277; UL 2277; UL and CSA approval

Cables designed for static application, .

#### Applications:

- Machine tools
- Wood machines
- Marble working machines
- Robotics
- Industrial sector

#### Approvals:

UL MTW UL1063  
 UL TC-ER 90°C 600V UL1277  
 UL WTTTC 90°C 1000V UL2277  
 UL DP-1  
 ULAWM 600V UL758  
 C(UL) CIC/TC

## CHARACTERISTICS

### Construction characteristics

Construction type	4G1
Conductor material	Annealed copper
Insulation	-
Insulation colour	Black w. number + yellow/green
Outer sheath	Special PVC compound
Sheath colour	Black

### Dimensional characteristics

Conductor cross-section	1 mm <sup>2</sup>
Number of cores	4



Operating temp.  
 -5 ... 90 °C



Flame retardant  
 UL 1581 SEC. 1160 AND CSA FT4



Oil resistance  
 Yes

**Dimensional characteristics**

Outer Diameter	7.9 mm
Copper content	38 kg/km
Approximate weight	107 kg/km

**Electrical characteristics**

Rated Voltage U <sub>0</sub> /U	600 V
Test voltage	2000 V

**Usage characteristics**

Field of application	Fixed installations
Operating temperature, range	-5 ... 90 °C
Minimum bending radius, static (XD)	15
Flame retardant	UL 1581 SEC. 1160 AND CSA FT4
Oil resistance	Yes



Operating temp.  
-5 ... 90 °C



Flame retardant  
UL 1581 SEC. 1160 AND CSA FT4



Oil resistance  
Yes