



Control- or signal cable for dynamic application, PVC-jacket, shielded, oil resistant, flame retardant, UL and CSA approved

### STANDARDS

Product UL and CSA approval

**Reference:** 10554704  
**Country Ref.:** Q103410E100  
**EAN 13:** 8054803091026

### CONTACT

Market information  
industryprojects.business@lynxéo  
ogroup.com

## CHARACTERISTICS

### Construction characteristics

Construction type	(10x0,34)C
Conductor material	Bare copper
Insulation	Polyolefin
Insulation colour	DIN 47100
Taping	Non woven tape
Shielding	≥85% tinned copper braid coverage
Outer sheath	PVC
Sheath colour	Grey RAL 7001

### Dimensional characteristics

Conductor cross-section	0.34 mm <sup>2</sup>
Number of cores	10
Outer Diameter	7.3 mm



Storage temperature, range  
-30 ... 80 °C



Operating temp.  
-5 ... 80 °C



Flame retardant  
IEC/EN 60332-1-2; FT1; UL 1581 FT1



Oil resistance  
EN 50363-4-1

**Dimensional characteristics**

Copper content	46.8 kg/km
Approximate weight	77 kg/km

**Electrical characteristics**

Rated Voltage U <sub>0</sub> /U	300 V
Test voltage	1500 V

**Mechanical characteristics**

Bending cycles	5 Mio.
Speed	300 m/min
Maximum acceleration	20 m/s <sup>2</sup>

**Usage characteristics**

Field of application	Dynamic
Storage temperature, range	-30 ... 80 °C
Operating temperature, range	-5 ... 80 °C
Minimum dynamic operating bending radius	6.5 (xD)
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1
Oil resistance	EN 50363-4-1



Storage temperature, range  
-30 ... 80 °C



Operating temp.  
-5 ... 80 °C



Flame retardant  
IEC/EN 60332-1-2; FT1; UL 1581 FT1



Oil resistance  
EN 50363-4-1