



Control- or signal cable for dynamic application, PVC-jacket, shielded, oil resistant, flame retardant, UL and CSA approved

### STANDARDS

Product UL and CSA approval

**Reference:** 10554864  
**Country Ref.:** Q103404E100  
**EAN 13:** 8054803087821

### CONTACT

Market information  
industryprojects.business@lynx<sup>eo</sup>  
ogroup.com

## CHARACTERISTICS

### Construction characteristics

|                    |                                   |
|--------------------|-----------------------------------|
| Construction type  | (4x0,34)C                         |
| Conductor material | Bare copper                       |
| Insulation         | Polyolefin                        |
| Insulation colour  | DIN 47100                         |
| Taping             | Non woven tape                    |
| Shielding          | ≥85% tinned copper braid coverage |
| Outer sheath       | PVC                               |
| Sheath colour      | Grey RAL 7001                     |

### Dimensional characteristics

|                         |                      |
|-------------------------|----------------------|
| Conductor cross-section | 0.34 mm <sup>2</sup> |
| Number of cores         | 4                    |
| Outer Diameter          | 5.1 mm               |



Storage temperature, range  
-30 ... 80 °C



Operating temp.  
-5 ... 80 °C



Flame retardant  
IEC/EN 60332-1-2; FT1; UL 1581 FT1



Oil resistance  
EN 50363-4-1

**Dimensional characteristics**

|                    |            |
|--------------------|------------|
| Copper content     | 21.7 kg/km |
| Approximate weight | 39 kg/km   |

**Electrical characteristics**

|                                 |        |
|---------------------------------|--------|
| Rated Voltage U <sub>0</sub> /U | 300 V  |
| Test voltage                    | 1500 V |

**Mechanical characteristics**

|                      |                     |
|----------------------|---------------------|
| Bending cycles       | 5 Mio.              |
| Speed                | 300 m/min           |
| Maximum acceleration | 20 m/s <sup>2</sup> |

**Usage characteristics**

|  |                                    |
|--|------------------------------------|
| Field of application                     | Dynamic                            |
| Storage temperature, range               | -30 ... 80 °C                      |
| Operating temperature, range             | -5 ... 80 °C                       |
| Minimum dynamic operating bending radius | 6.5 (xD)                           |
| Flame retardant                          | IEC/EN 60332-1-2; FT1; UL 1581 FT1 |
| Oil resistance                           | EN 50363-4-1                       |



Storage temperature, range  
-30 ... 80 °C



Operating temp.  
-5 ... 80 °C



Flame retardant  
IEC/EN 60332-1-2; FT1; UL 1581 FT1



Oil resistance  
EN 50363-4-1