



**Reference:** 10554955  
**Country Ref.:** Q202502E100  
**EAN 13:** 8054803086008

**CONTACT**

Market information  
 industryprojects.business@lynxéogroup.com

Twisted pair (TP) control cables for data and signal transmission in dynamic application and use in drag chains, PVC jacket, shielded, oil resistant, flame retardant, UL and CSA approved

**STANDARDS**

**Product** UL and CSA approval

Cables designed for continuous moving application, high flexible, oil resistance.

**Applications:**

- Tracksystems for tool machines
- Wood machines
- Automatic lines for assembly
- Handling
- Packaging
- Other applications with moderate stresses

**CHARACTERISTICS**

**Construction characteristics**

Construction type	(2x2x0,25)C
Conductor material	Bare copper
Insulation	Polyolefin
Insulation colour	DIN 47100
Taping	Non woven tape
Shielding	≥85% tinned copper braid coverage
Outer sheath	PVC
Sheath colour	Grey RAL 7001

**Dimensional characteristics**

Conductor cross-section	0.25 mm <sup>2</sup>
Number of cores	4
Outer Diameter	5.7 mm



Operating temp.  
 -5 ... 80 °C



Storage temperature, range  
 -30 ... 80 °C



Flame retardant  
 IEC/EN 60332-1-2; FT1; UL 1581 FT1



Oil resistance  
 EN 50363-4-1

**Dimensional characteristics**

Copper content	20.8 kg/km
Approximate weight	45 kg/km

**Electrical characteristics**

Rated Voltage U <sub>0</sub> /U	300 V
Test voltage	1500 V

**Mechanical characteristics**

Bending cycles	5 Mio.
Speed	300 m/min
Maximum acceleration	20 m/s <sup>2</sup>

**Usage characteristics**

Field of application	Dynamic
Operating temperature, range	-5 ... 80 °C
Storage temperature, range	-30 ... 80 °C
Minimum dynamic operating bending radius	6.5 (xD)
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1
Oil resistance	EN 50363-4-1



Operating temp.  
-5 ... 80 °C



Storage temperature, range  
-30 ... 80 °C



Flame retardant  
IEC/EN 60332-1-2; FT1; UL 1581 FT1



Oil resistance  
EN 50363-4-1