



**Reference:** 10577149  
**Country Ref.:** F125004V100

#### CONTACT

Market information  
 industryprojects.business@lynxgroup.com

TPU-Control cables with low capacity insulation for extremely dynamic application, up to 1000V, PUR jacket, unshielded, oil resistant, halogen free, UL and CSA approved

#### STANDARDS

**Product** UL and CSA approval

### CHARACTERISTICS

#### Construction characteristics

|                    |                                |
|--------------------|--------------------------------|
| Construction type  | 4G2,5                          |
| Conductor material | Bare copper                    |
| Insulation         | Polyolefin                     |
| Insulation colour  | Black w. number + yellow/green |
| Taping             | Non woven tape                 |
| Outer sheath       | PUR                            |
| Sheath colour      | Grey RAL 7001                  |
| Halogen free       | Yes                            |

#### Dimensional characteristics

|                         |                     |
|-------------------------|---------------------|
| Number of cores         | 4                   |
| Conductor cross-section | 2.5 mm <sup>2</sup> |
| Outer Diameter          | 8.7 mm              |
| Copper content          | 100 kg/km           |



Halogen free  
 Yes



Operating temp.  
 -30 ... 80 °C



Storage temperature, range  
 -40 ... 80 °C



Oil resistance  
 EN 50363-10-2



Flame retardant  
 IEC/EN 60332-1-2; FT1; UL 1581 FT1

**Dimensional characteristics**

Approximate weight 127 kg/km

**Electrical characteristics**

Rated Voltage U<sub>0</sub>/U 1000 V  
 Test voltage 4000 V

**Mechanical characteristics**

Bending cycles 10 Mio.  
 Speed 600 m/min  
 Maximum acceleration 60 m/s<sup>2</sup>

**Usage characteristics**

Field of application Dynamic  
 Minimum dynamic operating bending radius 6.5 (xD)  
 Operating temperature, range -30 ... 80 °C  
 Storage temperature, range -40 ... 80 °C  
 Oil resistance EN 50363-10-2  
 Flame retardant IEC/EN 60332-1-2; FT1; UL 1581 FT1



Halogen free  
Yes



Operating temp.  
-30 ... 80 °C



Storage temperature, range  
-40 ... 80 °C



Oil resistance  
EN 50363-10-2



Flame retardant  
IEC/EN 60332-1-2; FT1; UL 1581 FT1