



Reference: 13-DRX24P02R
Country Ref.: 13-DRX24P02R

CONTACT

Market information
 industryprojects.business@lynxeogroup.com

CAN-BUS cables with PVC jacket for fixed installation, shielded, flame retardant

STANDARDS

Product UL and CSA approval

APPLICATIONS

Interconnecting fieldbus cable for static application
 BUS cables to connect Controller Area Network components

Normative references

CAN standard and customers requirements
UL recognized / CSA approval



Operating temp.
 -20 ... 80 °C



Storage temperature, range
 -30 ... 80 °C



Flame retardant
 IEC/EN 60332-1-2; FT1; UL 1581 FT1

CHARACTERISTICS**Construction characteristics**

Construction type	(2x2x0.22)C
Conductor material	Bare copper
Insulation	Foam-skin
Insulation colour	DIN 47100
Taping	Soft tape
Shielding	≥85% tinned copper braid coverage
Outer sheath	PVC
Sheath colour	Violet RAL 4001

Dimensional characteristics

Nominal outer diameter	7.6 mm
Copper content	35 kg/km
Approximate weight	69 kg/km

Electrical characteristics

Rated Voltage U ₀ /U	300 V
Characteristic impedance	120 Ohm
Test voltage	1500 V

Transmission characteristics

Attenuation at 1 MHz	1.3 dB/100m
Attenuation at 5 MHz	3.1 dB/100m
Attenuation at 10 MHz	4.3 dB/100m
Attenuation at 20 MHz	6.4 dB/100m

Usage characteristics

Field of application	Static
Operating temperature, range	-20 ... 80 °C
Storage temperature, range	-30 ... 80 °C
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1