



Reference: 13 - ELW09G03R - C1

Country Ref.: 13 - ELW09G03R - C1

CONTACT

Market information
industryprojects.business@lynxgroup.com

Power supply multiconductor cables for dynamic application with PVC jacket, unshielded, resistant to oils, flame retardant, MTW

STANDARDS

Product UL and CSA approval

Normative Reference:

UL and CSA approval
AWM 80 ° C - 600V/1000V
AWM 80 ° C - 600V/1000V FT1
MTW 90 ° C - 600V

Oil resistance:

IEC 50363 - 4 - 1

Refrigerant oil resistance:

CNOMO E.03.40.150

NFT 46 - 013

Flame retardant:

IEC 60332 - 1 - 2

FT1

UL 1581

EN 50265 - 2 - 1

Core identification

4x U/L1/C/L + V/L2 W/L37D/L - Yellow/Green
7 x Black numerated Yellow/Green



Operating temp.
-25 ... 80 ° C



Storage temperature, range
-30 ... 80 ° C



IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1
EN 50363 - 4 - 1



Oil resistance
EN 50363 - 4 - 1

CHARACTERISTICS

	3G6
	Stranded bare copper
Taping	Soft tape
Insulation colour	Black w. number + yellow/green
Sheath colour	Grey RAL 7001
	-
	1.5 mm ²
Nominal outer diameter	14.5 mm
Copper content	173 kg/km
()	110 kg/km
Rated Voltage U ₀ /U	0.6/1 kV
	4000 V
Maximum acceleration	10 m/s ²
Minimum bending cycles	5 Mio.
Speed	180 m/min
Field of application	Dynamic
Minimum dynamic operating bending radius	10 (xD)
操作度范	- 25 ... 80 °C
Storage temperature, range	- 30 ... 80 °C
	IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1
Oil resistance	EN 50363 - 4 - 1