



**Reference:** 13-MHM22P05P-V1  
**Country Ref.:** 13-MHM22P05P-V1

**CONTACT**

Market information  
 industryprojects.business@lynxéogroup.com

resolver cables for extremely dynamic applications, PUR jacket, shielded, oil resistant, flame retardant, halogen free

**STANDARDS**

**Product** UL and CSA approval

**TYPE APPROVAL UL/CSA**

AWM 80°C -30V  
 AWM 75°C - 30V FT1

**Oil Resistance:**

VDE 0472 p. 803 A7B (04 1986);

UL 1581 VDE 0282 part 10;

HD 22.10 S1

**Note :** Cables can be supplied in "non-halogen" version

**CHARACTERISTICS**

**Construction characteristics**

Conductor material	Tinned copper
Construction type	(5x(2x0.34)C)C
Insulation	PVC
Insulation colour	TAB CP2
Individual screen	Tinned copper braid
Individual sheath	PVC
Shielding	≥85% tinned copper braid coverage
Outer sheath	PUR
Sheath colour	Green RAL 6018
Halogen free	Yes

**Dimensional characteristics**

Nominal outer diameter	11.2 mm
------------------------	---------



Halogen free  
 Yes



Operating temp.  
 -30 ... 80 °C



Storage temperature, range  
 -40 ... 80 °C



Oil resistance  
 EN 50363-10-2



Flame retardant  
 IEC/EN 60332-1-2; FT1; UL 1581 FT1

Dimensional characteristics	
Copper content	112 kg/km
Approximate weight	205 kg/km
Electrical characteristics	
Rated Voltage U <sub>0</sub> /U	300 V
Test voltage	1500 V
Mechanical characteristics	
Maximum acceleration	20 m/s <sup>2</sup>
Bending cycles	10 Mio.
Speed	240 m/min
Usage characteristics	
Field of application	Dynamic
Minimum dynamic operating bending radius	7.5 (xD)
Operating temperature, range	-30 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Oil resistance	EN 50363-10-2
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1



Halogen free  
Yes



Operating temp.  
-30 ... 80 °C



Storage temperature, range  
-40 ... 80 °C



Oil resistance  
EN 50363-10-2



Flame retardant  
IEC/EN 60332-1-2; FT1; UL 1581 FT1