



Single core power cables for extremely dynamic applications MOTIONLINE® PREMIUM

STANDARDS

Product UL and CSA approval

Single core power cables for extremely dynamic applications; PUR jacket, TPM insulation, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.

Reference: 49347117

CONTACT

Market information
industryprojects.business@lynxéo.com
ogroup.com



Halogen free
Yes



Operating temp.
-30 ... 80 °C



Storage temperature, range
-50 ... 80 °C



Flame retardant
IEC 60332-1-2; UL 1581 FT1



Oil resistance
DIN EN 50363-10-2 & DIN EN 60811-404

CHARACTERISTICS**Construction characteristics**

Construction type	1x35
Conductor material	Bending-resistant conductor with bare copper wires
Insulation	TPM with very low capacitance
Insulation colour	Yellow/Green
Outer sheath	PUR
Sheath colour	Orange RAL 2003
Halogen free	Yes

Dimensional characteristics

Copper content	340 kg/km
Approximate weight	394 kg/km
Outer Diameter	12.4 mm

Electrical characteristics

Rated Voltage U ₀ /U	0.6/1 kV
Test voltage	4000 V

Mechanical characteristics

Bending cycles	5 Mio.
Speed	300 m/min
Maximum acceleration	50 m/s ²

Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	7.5 (xD)
Operating temperature, range	-30 ... 80 °C
Storage temperature, range	-50 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404