



Single core power cables for extremely dynamic applications MOTIONLINE® PREMIUM

STANDARDS

Product UL and CSA approval

Single core power cables for extremely dynamic applications; PUR jacket, TPM insulation, screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC - and halogen - free.

Reference: 49364660

CONTACT

Market information
 industryprojects.business@lynxéogroup.com



Halogen free



Operating temp.
 - 30 ... 80 °C



Storage temperature, range
 - 50 ... 80 °C



IEC 60332 - 1 - 2; UL 1581 FT1



Oil resistance
 DIN EN 50363 - 10 - 2 & DIN EN 60811 - 404

CHARACTERISTICS

	(1x50)C
	Bending - resistant conductor with bare copper wires
	TPM with very low capacitance
	Tinned copper braid, coverage 80%
	PUR
Sheath colour	Orange RAL 2003
Halogen free	
Copper content	541 kg/km
()	605 kg/km
	15.1 mm
Rated Voltage U ₀ /U	0.6/1 kV
	4000 V
Bending cycles	10 Mio.
Speed	300 m/min
Maximum acceleration	50 m/s ²
Field of application	Dynamic
Minimum dynamic operating bending radius	7.5 (xD)
操作度范	- 30 ... 80 ° C
Storage temperature, range	- 50 ... 80 ° C
	IEC 60332 - 1 - 2; UL 1581 FT1
Oil resistance	DIN EN 50363 - 10 - 2 & DIN EN 60811 - 404