



Measuring systems cables for very dynamic applications. MOTIONLINE®
ADVANCED

STANDARDS

Product UL and CSA approval

For very dynamic applications; PUR Jacket, screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC - and halogen - free.

Reference: 49389260
Country Ref.: IN 532

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com



Halogen free



Operating temp.
- 15 ... 80 °C



Storage temperature, range
- 40 ... 80 °C



IEC 60332 - 1 - 2; UL 1581 FT1
Oil resistance
DIN EN 50363 - 10 - 2 & DIN EN 60811 - 404



CHARACTERISTICS

	(4x2x0,14+4x1,0+(4x0,14)C)C
	Bending - resistant conductor with tinned copper wires
	TPM with very low capacitance
Insulation colour	See Tab
	Tinned copper braid, coverage 80%
	PUR
Sheath colour	Orange RAL 2003
Halogen free	
	9.1 mm
Copper content	88 kg/km
()	131 kg/km
Rated Voltage U _o /U	30 V
	300 V
Bending cycles	10 Mio.
Speed	180 m/min
Maximum acceleration	20 m/s ²
Field of application	Dynamic
Minimum dynamic operating bending radius	10 (xD)
操作度范	- 15 ... 80 ° C
Storage temperature, range	- 40 ... 80 ° C
	IEC 60332 - 1 - 2; UL 1581 FT1
Oil resistance	DIN EN 50363 - 10 - 2 & DIN EN 60811 - 404