



Reference: 49475160

#### CONTACT

Market information  
industryprojects.business@lyn  
xeogroup.com

Servo cables for extremely dynamic applications. MOTIONLINE® ADVANCED

#### STANDARDS

Product UL and CSA approval

Servo cables for very dynamic applications; PUR Jacket; screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.



无卤  
是



操作温度  
-15 ... 80 °C



存储温度范围  
- °C



阻燃 - 火焰  
IEC 60332-1-2; UL 1581 FT1



耐油  
DIN EN 50363-10-2 & DIN EN 60811-404

## CHARACTERISTICS

## 结构特性

结构类型	4G2.5 C
导体材料	Bending-resistant conductor with bare copper wires
绝缘	TPM with very low capacitance
绞合	Power cores stranded with filler
绝缘色	Black - white marking U/L1/C/L + V/L2 W/L3/D/L - Yellow/ Green
屏蔽	Tinned copper braid, coverage $\geq$ 85%
外护套	PUR
护套颜色	Orange RAL 2003
无卤	是

## 尺寸特性

外径	9.9 mm
铜含量	120 kg/km
近似重量	165 kg/km

## 电气特性

Rated Voltage U <sub>0</sub> /U	0.6/1 kV
测试电压	4000 V

## 机械特性

弯曲循环	10 Mio.
速度	180 m/min
Maximum acceleration	20 m/s <sup>2</sup>

## 使用特性

应用类型	动态
最小弯曲半径 - 动态	10 (xD)
操作温度范围	-15 ... 80 °C
存储温度范围	- °C
阻燃 - 火焰	IEC 60332-1-2; UL 1581 FT1
耐油	DIN EN 50363-10-2 & DIN EN 60811-404