



Reference: 49475260

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

Servo cables for extremely dynamic applications. MOTIONLINE® ADVANCED

STANDARDS

Product UL and CSA approval

Servo cables for very dynamic applications; PUR Jacket; screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.



无卤
是



操作温度
-15 ... 80 °C



存储温度范围
- °C



阻燃 - 火焰
IEC 60332-1-2; UL 1581 FT1



耐油
DIN EN 50363-10-2 & DIN EN 60811-404

CHARACTERISTICS

结构特性

结构类型	4G4 C
导体材料	Bending-resistant conductor with bare copper wires
绝缘	TPM with very low capacitance
绞合	Power cores stranded with filler
绝缘色	Black - white marking U/L1/C/L + V/L2 W/L3/D/L - Yellow/ Green
屏蔽	Tinned copper braid, coverage \geq 85%
外护套	PUR
护套颜色	Orange RAL 2003
无卤	是

尺寸特性

外径	11.5 mm
铜含量	193 kg/km
近似重量	245 kg/km

电气特性

Rated Voltage U ₀ /U	0.6/1 kV
测试电压	4000 V

机械特性

弯曲循环	10 Mio.
速度	180 m/min
Maximum acceleration	20 m/s ²

使用特性

应用类型	动态
最小弯曲半径 - 动态	10 (xD)
操作温度范围	-15 ... 80 ° C
存储温度范围	- ° C
阻燃 - 火焰	IEC 60332-1-2; UL 1581 FT1
耐油	DIN EN 50363-10-2 & DIN EN 60811-404