



Measuring systems cables for very dynamic applications. MOTIONLINE® ADVANCED

STANDARDS

Product UL and CSA approval

For very dynamic applications; PUR Jacket, screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.

Reference: 49482671

Country Ref.: 6FX8008-1BD21

CONTACT

Market information
industryprojects.business@lynx
ogroup.com



Halogen free
Yes



Operating temp.
-15 ... 80 °C



Storage temperature, range
-40 ... 80 °C



Flame retardant
IEC 60332-1-2; UL 1581 FT1



Oil resistance
DIN EN 50363-10-2 & DIN EN 60811-404

CHARACTERISTICS**Construction characteristics**

Construction type	(4x2x0,34+4x0,5)C
Conductor material	Bending-resistant conductor with tinned copper wires
Insulation	TPM with very low capacitance
Insulation colour	See Tab
Screen	Tinned copper braid, coverage ≥ 85%
Outer sheath	PUR
Sheath colour	Green RAL 6018
Halogen free	Yes

Dimensional characteristics

Copper content	70 kg/km
Approximate weight	107 kg/km
Outer Diameter	8.6 mm

Electrical characteristics

Rated Voltage U ₀ /U	30 V
Test voltage	300 V

Mechanical characteristics

Bending cycles	5 Mio.
Speed	180 m/min
Maximum acceleration	20 m/s ²

Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	10 (xD)
Operating temperature, range	-15 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404