



Servo cables for extremely dynamic applications with control pair MOTIONLINE® PREMIUM

## STANDARDS

**Product** UL and CSA approval

Servo cables with control pair for extremely dynamic applications; PUR Jacket; screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.

**Reference:** 49494161

**Country Ref.:** 6FX8008-1BA21-Plus

## CONTACT

Market information  
industryprojects.business@lynx<sup>eo</sup>  
ogroup.com



Halogen free  
Yes



Operating temp.  
-30 ... 80 °C



Storage temperature, range  
-50 ... 80 °C



Flame retardant  
IEC 60332-1-2; UL 1581 FT1



Oil resistance  
DIN EN 50363-10-2 & DIN EN 60811-404

## CHARACTERISTICS

### Construction characteristics

Construction type	(4G2.5 + (2x1.5)C)C
Conductor material	Bending-resistant conductor with bare copper wires
Insulation	TPM with very low capacitance
Lay Up	power cores and control pairs stranded with filler
Insulation colour	Power: Black - White marking U/L1/C/L+ V/L2 W/L3/D/L- Yellow/ Green; Signal: Black+White
Individual screen	Signal shield: Tinned copper braid, coverage $\geq 80\%$
Screen	Tinned copper braid, coverage $\geq 85\%$
Outer sheath	PUR
Sheath colour	Orange RAL 2003
Halogen free	Yes

### Dimensional characteristics

Outer Diameter	13.3 mm
Copper content	182 kg/km
Approximate weight	265 kg/km

### Electrical characteristics

Rated Voltage U <sub>o</sub> /U	0.6/1 kV
Test voltage	4000 V

### Mechanical characteristics

Bending cycles	10 Mio.
Speed	300 m/min
Maximum acceleration	50 m/s <sup>2</sup>

### Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	7.5 (xD)
Operating temperature, range	-30 ... 80 °C
Storage temperature, range	-50 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404