



Reference: 49494661
Country Ref.: 6FX8008-1BA25-Plus

CONTACT

Market information
industryprojects.business@lynx^{eo}.com
ogroup.com

Servo cables for extremely dynamic applications with control pair MOTIONLINE® PREMIUM

STANDARDS

Product UL and CSA approval

Servo cables with control pair for extremely dynamic applications; PUR Jacket; screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.



Halogen free
Yes



Operating temp.
-30 ... 80 °C



Storage temperature, range
-50 ... 80 °C



Flame retardant
IEC 60332-1-2; UL 1581 FT1



Oil resistance
DIN EN 50363-10-2 & DIN EN 60811-404

CHARACTERISTICS

Construction characteristics

Construction type	(4G25 +(2x1.5)C)C
Conductor material	Bending-resistant conductor with bare copper wires
Insulation	TPM with very low capacitance
Lay Up	power cores and control pairs stranded with filler
Insulation colour	Power: Black - White marking U/L1/C/L+ V/L2 W/L3/D/L- Yellow/ Green; Signal: Black+White
Individual screen	Signal shield: Tinned copper braid, coverage >=80%
Screen	Tinned copper braid, coverage ≥ 85%
Outer sheath	PUR
Sheath colour	Orange RAL 2003
Halogen free	Yes

Dimensional characteristics

Outer Diameter	26.8 mm
Copper content	1070 kg/km
Approximate weight	1377 kg/km

Electrical characteristics

Rated Voltage U _o /U	0.6/1 kV
Test voltage	4000 V

Mechanical characteristics

Bending cycles	10 Mio.
Speed	300 m/min
Maximum acceleration	50 m/s ²

Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	7.5 (xD)
Operating temperature, range	-30 ... 80 °C
Storage temperature, range	-50 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404