



Reference: 71320703

CONTACT

Market information
industryprojects.business@lynxéo
ogroup.com

Torsion resistant low-voltage cable for free hanging of max. 100 m

STANDARDS

Product EN 50363; HD 22-13; IEC 60228; IEC 60502

APPLICATIONS

Low-voltage loop cable WINDLINK LV-RS (N)HXCSLOE was developed for special application condition in wind turbines. The construction is torsion resistant by free hanging of max.100 m. These cables are specified for medium mechanical stress and for operation under permanent influence of sea water and usage outdoor.

Resistance to

- permanent movement
- permanent vibrations
- compressive stress
- oil, EN60811-2-1, ASTM No.2, 24 h at 100 °C
- low smoke, IEC 61034, >50 %
- halogen-free IEC 60754
- permanent influence of seawater
- ozone influence, EN 60811-2-1 clause 8
- suitable for torsion of max. 6 counterclockwise rotations and min. free hanging up from 25 m

Design

Core

Conductor

- Copper, plain, flexible concentrically stranded circular

Insulation

- Extruded halogen-free rubber compound EI8 acc. to EN 50363-5

Screen

- Tinned wire copper braid, covering min. 80 %

Outer Sheath

- Extruded halogen-free EVA compound EM8 acc. to EN 50363-6

CHARACTERISTICS

Construction characteristics

Conductor material	Plain annealed copper
Conductor flexibility	Flexible class 5
Insulation	Rubber
Outer sheath	Rubber compound
Sheath colour	Black
Halogen free	IEC 60754-2
Overall screen	-
With Green/Yellow core	Yes

Dimensional characteristics

Number of cores	25
Conductor cross-section	1 mm ²
Copper content	0 kg/km
Nominal outer diameter	20.0 mm
Approximate weight	550 kg/km

Electrical characteristics

Rated Voltage U _o /U (U _m)	0,6/1 kV
---	----------

Usage characteristics

Flame retardant	EN 50265-2-1
Silicone free	Yes
RoHS compliant	-
Max. conductor temperature in service	- °C
Weather resistance	-
Short-circuit max. conductor temperature	- °C

SELLING AND DELIVERY INFORMATION

Inkjet marking e.g.: WINDLINK LV-RS (N)HXCSLOE 0.6/1 kV | NEXANS I