



Reference: 79462301

### CONTACT

Markets and Products Information  
[rollingstock.business@lynxeogroup.com](mailto:rollingstock.business@lynxeogroup.com)

### SINGLE CORE POWER CABLES

FLAMEX® EN 50264-3-1 600V M power cables are used for fixed and protected installations. This product range is recommended for narrow spaces where an optimal bending radius is required. FLAMEX® cables are designed to withstand tough working conditions (oil, ozone, temperature variation, etc.). 120° C conductor temperature is allowed for a 20,000 hours cumulative working time.

### STANDARDS

Product EN 50264-3-1; EN 45545 - HL3; IEC 60228



导线柔软度  
柔软等级5



无卤  
EN 60754-1 & EN 60684-2



额定电压U<sub>0</sub>/U  
0.6/ 1 (1.2) kV



阻燃 - 火焰  
IEC 60332-1-2



阻燃  
EN IEC 60332-3-24  
(cat C); EN IEC 60332-3-25  
(EN50305)



烟密度  
EN/IEC 61034-2



气体毒性  
EN 50305-9.2



操作温度  
-40 ... 90 ° C

## CHARACTERISTICS

## 结构特性

导体材料	Tin plated copper
导线柔软度	柔软等级5
绝缘	Cross-linked compound
无卤	EN 60754-1 & EN 60684-2

## 尺寸特性

导线截面	1.5 mm <sup>2</sup>
外径最小值	2.8 mm
Maximum outer diameter	3.2 mm
近似重量	20 kg/km
导线直径	- mm

## 电气特性

额定电压U <sub>0</sub> /U	0.6/ 1 (1.2) kV
-----------------------	-----------------

## 使用特性

阻燃 - 火焰	IEC 60332-1-2
阻燃	EN IEC 60332-3-24 (cat C); EN IEC 60332-3-25 (EN50305)
烟密度	EN/IEC 61034-2
气体毒性	EN 50305-9.2
操作温度范围	-40 ... 90 °C
芯线最高静止温度	90 °C
Overload maximum core temperature	- °C
耐化学物质	好
Ozone resistance	是
抗UV	是
短路最高线芯温度	200 °C