



**Reference:** ABS 1356 VNA 20

### CONTACT

Market information  
industryprojects.business@lynx  
ogroup.com

**International Designation:** ABS 1356 VNA 20 AWG

**Designed for general purpose aircraft wiring applications.**

Screened and Jacketed Single and Multicores  
UV Laser Printable

### STANDARDS

**Produkt** ABS 1356

**Tests** prEN 3475

### DESIGN CONSTRUCTION

#### CONDUCTOR

1 cores ABS 0949 AD

Nickel Copper Clad Aluminium

#### SCREEN

Nickel-plated copper spiral screen

#### JACKET

Polymide tape

UV PTFE tape

### IDENTIFICATION

1 core (VNA) : Grey

**Marking text :** " XXX \*\* FR F++ "

Colour : Green for AWG 22, 18, 14 and 10 - Blue for AWG 24, 20, 16 and 12

### JACKET IDENTIFICATION



Betriebstemp.  
-65 ... 180 °C



Ölbeständig  
Very good resistance to aircraft fluids



RoHS konform  
ja

## CHARACTERISTICS

**Konstruktionsmerkmale**

Aderkennzeichnung	Grey
Anzahl Leiter	1
Isolationsmaterial	-
Jacket color	Grey
Jacket material	Polyimide tape, UV PTFE tape
Leitermaterial	Nickel Copper Clad Aluminum
Schirm	Nickel plated copper spiral screen

**Abmessungsmerkmale**

Außendurchmesser, nom.	1,78 mm
Abmessung (AWG)	20
Screen strands nominal diameter	0,08 mm
Max. Gewicht	7,75 g/m
Aderanzahl	1
Conductor stranding	-
Max. Kerndurchmesser	- mm
Maximaler Außendurchmesser	1,87 mm
Nominal weight	7,48 g/m

**Elektrische Eigenschaften**

Betriebsspannung	600 V
Maximale Betriebsfrequenz	0,0002 MHz
Maximum DC resistance at 20°C	49,6 Ohm/100m

**Anwendungsmerkmale**

Betriebstemperatur	-65 ... 180 °C
Ölbeständig	Very good resistance to aircraft fluids
Arc tracking resistant	Ja
RoHS konform	ja