



**Reference:** EN 2267-009B 001P  
(DRB 26)

**Country Ref.:** 10066375

### CONTACT

Market information  
industryprojects.business@lynxeo.com  
ogroup.com

**International Designation:** DRB 26 001

**Designed for general Purpose Aircraft Wiring Applications.**

Multicores DRA

### STANDARDS

**Producto** EN 2267-009

**Ensayo** prEN 3475

### DESIGN CONSTRUCTION

#### CORES

2, 3 or 4 cores EN2267-009A

### IDENTIFICATION

Colours of cores : See table in this datasheet

Colours of marking: White for red and green core, green for blue and yellow cores

Marking : EN DRA \*\* FR F ++

DRA = short designation

\*\* = AWG

FR = Country of origin (FR = France)

F = Manufacturer (F = Lynxeo)

++ = Year of production (i.e. 14 = 2014)

## CHARACTERISTICS

### Características de construcción

Color	P
Type of conductor	-
Core identification	Red, Blue
Number of conductors	-
Size code	-

### Características dimensionales

Diámetro exterior máximo	1,68 mm
Diámetro exterior nominal	1,56 mm
Número de conductores	2
Maximum weight	4,28 g/m



No propagación de la llama  
FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Resistencia a aceites  
Very good resistance to aircraft fluids



Acorde con normativa RoHS  
Si



Temp. ambiente de utilización  
-55 ... 260 °C

### Características dimensionales

Nominal weight 3,98 g/m

### Características eléctricas

Maximal operating frequency 0,002 MHz

Maximum DC resistance at 20°C 165 Ohm/100m

Tensión de operación 600 V

### Características de uso

No propagación de la llama FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)

Resistencia a aceites Very good resistance to aircraft fluids

Arc tracking resistant Yes

Acorde con normativa RoHS Si

Temperatura ambiente de utilización (rango) -55 ... 260 °C

## IDENTIFICATION

Colours of cores : See table in this datasheet  
 Colours of marking : White for red and green core, green for blue and yellow cores  
 Marking : EN DRA \*\* FR F ++  
 DRA = short designation  
 \*\* = AWG  
 FR = Country of origin (FR = France)  
 F = Manufacturer (F = Lynxéo)  
 ++ = Year of production (i.e. 14 = 2014)



No propagación de la llama  
 FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Resistencia a aceites  
 Very good resistance to aircraft fluids



Acorde con normativa RoHS  
 Si



Temp. ambiente de utilización  
 -55 ... 260 °C