



Reference: EN 2267-009B 001P
(DRB 6)

CONTACT

Market information
industryprojects.business@lynxéogroup.com

International Designation: DRB 6 140

Designed for general Purpose Aircraft Wiring Applications.

Multicores DRA

STANDARDS

Produkt EN 2267-009

Tests prEN 3475

DESIGN CONSTRUCTION

CORES

2, 3 or 4 cores EN2267-009A

IDENTIFICATION

Colours of cores : See table in this datasheet

Colours of marking: White for red and green core, green for blue and yellow cores

Marking : EN DRA ** FR F ++

DRA = short designation

** = AWG

FR = Country of origin (FR = France)

F = Manufacturer (F = Lynxéo)

++ = Year of production (i.e. 14 = 2014)

CHARACTERISTICS

Konstruktionsmerkmale

Farbe	P
Leitertyp	-
Aderkennzeichnung	Red, Blue
Anzahl Leiter	-
Size code	-

Abmessungsmerkmale

Maximaler Außendurchmesser	11,4 mm
Außendurchmesser, nom.	11,1 mm
Aderanzahl	2
Max. Gewicht	278,1 g/m



Flammwidrig
FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Ölbeständig
Very good resistance to aircraft fluids



RoHS konform
ja



Betriebstemp.
-55 ... 260 °C

Abmessungsmerkmale

Nominal weight 270,12 g/m

Elektrische Eigenschaften

Maximale Betriebsfrequenz 0,002 MHz

Maximum DC resistance at 20°C 1,63 Ohm/100m

Betriebsspannung 600 V

Anwendungsmerkmale

Flammwidrig FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)

Ölbeständig Very good resistance to aircraft fluids

Arc tracking resistant Ja

RoHS konform ja

Betriebstemperatur -55 ... 260 °C

IDENTIFICATION

Colours of cores
Colours of marking
Marking

: See table in this datasheet
: White for red and green core, green for blue and yellow cores
: EN DRA ** FR F ++
DRA = short designation
** = AWG
FR = Country of origin (FR = France)
F = Manufacturer (F = Lynxéo)
++ = Year of production (i.e. 14 = 2014)



Flammwidrig
FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Ölbeständig
Very good resistance to aircraft fluids



RoHS konform
ja



Betriebstemp.
-55 ... 260 °C