



**Reference:** EN 2267-009B 002P  
(DRB 24)

**Country Ref.:** 10066382

### CONTACT

Market information  
industryprojects.business@lynxéogroup.com

**International Designation:** DRB 24 002

**Designed for general Purpose Aircraft Wiring Applications.**

Multicores DRA

### STANDARDS

**Produkt** EN 2267-009

**Tests** prEN 3475

### DESIGN CONSTRUCTION

#### CORES

2, 3 or 4 cores EN2267-009A

### IDENTIFICATION

Colours of cores : See table in this datasheet

Colours of marking: White for red and green core, green for blue and yellow cores

Marking : EN DRA \*\* FR F ++

DRA = short designation

\*\* = AWG

FR = Country of origin (FR = France)

F = Manufacturer (F = Lynxéo)

++ = Year of production (i.e. 14 = 2014)

## CHARACTERISTICS

### Konstruktionsmerkmale

Farbe	P
Leitertyp	-
Aderkennzeichnung	Red, Blue
Anzahl Leiter	-
Size code	-

### Abmessungsmerkmale

Maximaler Außendurchmesser	1,92 mm
Außendurchmesser, nom.	1,82 mm
Aderanzahl	2
Max. Gewicht	5,6 g/m



Flammwidrig  
FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Ölbeständig  
Very good resistance to aircraft fluids



RoHS konform  
ja



Betriebstemp.  
-55 ... 260 °C

### Abmessungsmerkmale

Nominal weight 5,39 g/m

### Elektrische Eigenschaften

Maximale Betriebsfrequenz 0,002 MHz

Maximum DC resistance at 20°C 117 Ohm/100m

Betriebsspannung 600 V

### Anwendungsmerkmale

Flammwidrig FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)

Ölbeständig Very good resistance to aircraft fluids

Arc tracking resistant Ja

RoHS konform ja

Betriebstemperatur -55 ... 260 °C

## IDENTIFICATION

Colours of cores

: See table in this datasheet

Colours of marking

: White for red and green core, green for blue and yellow cores

Marking

: EN DRA \*\* FR F ++

DRA = short designation

\*\* = AWG

FR = Country of origin (FR = France)

F = Manufacturer (F = Lynxéo)

++ = Year of production (i.e. 14 = 2014)



Flammwidrig  
FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Ölbeständig  
Very good resistance to aircraft fluids



RoHS konform  
ja



Betriebstemp.  
-55 ... 260 °C