



Reference: EN 2267 - 009C
012P (DRC 16)
Country Ref.: 10117287

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

International Designation: DRC 16 012

Designed for general Purpose Aircraft Wiring Applications.

Multicores DRA

STANDARDS

Product EN 2267 - 009

Test prEN 3475

DESIGN CONSTRUCTION

CORES
2, 3 or 4 cores EN2267 - 009A

IDENTIFICATION

Colours of cores : See table in this datasheet
Colours of marking : White for red and green core, green for blue and yellow cores
Marking : EN DRA ** FR F ++
DRA = short designation
** = AWG
FR = Country of origin (FR = France)
F = Manufacturer (F = Lynxéo)
++ = Year of production (i.e. 14 = 2014)

CHARACTERISTICS

	P
Core identification	Red,Blue,Yellow
Number of conductors	-
Size code	-
Maximum outer diameter	4.13 mm
Nominal outer diameter	3.94 mm
	3
Maximum weight	45.14 g/m
Nominal weight	42.99 g/m



FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Oil resistance
Very good resistance to aircraft fluids



RoHS compliant
Yes



Operating temp.
-55 ... 260 °C

Maximal operating frequency	0.002 MHz
Maximum DC resistance at 20 ° C	14.9 Ohm/100m
Operating voltage	600 V

FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)

Oil resistance	Very good resistance to aircraft fluids
Arc tracking resistant	Yes
RoHS compliant	Yes
操作度范	- 55 ... 260 ° C

IDENTIFICATION

Colours of cores : See table in this datasheet
 Colours of marking : White for red and green core, green for blue and yellow cores
 Marking : EN DRA ** FR F ++
 DRA = short designation
 ** = AWG
 FR = Country of origin (FR = France)
 F = Manufacturer (F = Lynxéo)
 ++ = Year of production (i.e. 14 = 2014)



FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Oil resistance
Very good resistance to aircraft fluids



RoHS compliant
Yes



Operating temp.
- 55 ... 260 ° C