



Reference: EN 2267-009C 140P
(DRC 6)

Country Ref.: 10062790

CONTACT

Market information
industryprojects.business@lynxéogroup.com

International Designation: DRC 6 140

Designed for general Purpose Aircraft Wiring Applications.

Multicores DRA

STANDARDS

Produkt EN 2267-009

Tests prEN 3475

DESIGN CONSTRUCTION

CORES

2, 3 or 4 cores EN2267-009A

IDENTIFICATION

Colours of cores : See table in this datasheet

Colours of marking: White for red and green core, green for blue and yellow cores

Marking : EN DRA ** FR F ++

DRA = short designation

** = AWG

FR = Country of origin (FR = France)

F = Manufacturer (F = Lynxéo)

++ = Year of production (i.e. 14 = 2014)

CHARACTERISTICS

Konstruktionsmerkmale

Farbe	P
Leitertype	-
Aderkennzeichnung	Red,Blue,Yellow
Anzahl Leiter	-
Size code	-

Abmessungsmerkmale

Maximaler Außendurchmesser	12,26 mm
Außendurchmesser, nom.	11,96 mm
Aderanzahl	3
Max. Gewicht	417,15 g/m



Flammwidrig
FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Ölbeständig
Very good resistance to aircraft fluids



RoHS konform
ja



Betriebstemp.
-55 ... 260 °C

Abmessungsmerkmale

Nominal weight	405,17 g/m
----------------	------------

Elektrische Eigenschaften

Maximale Betriebsfrequenz	0,002 MHz
Maximum DC resistance at 20°C	1,63 Ohm/100m
Betriebsspannung	600 V

Anwendungsmerkmale

Flammwidrig	FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)
Ölbeständig	Very good resistance to aircraft fluids
Arc tracking resistant	Ja
RoHS konform	ja
Betriebstemperatur	-55 ... 260 °C

IDENTIFICATION

Colours of cores
Colours of marking
Marking

: See table in this datasheet
: White for red and green core, green for blue and yellow cores
: EN DRA ** FR F ++
DRA = short designation
** = AWG
FR = Country of origin (FR = France)
F = Manufacturer (F = Lynx^{eo})
++ = Year of production (i.e. 14 = 2014)



Flammwidrig
FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Ölbeständig
Very good resistance to aircraft fluids



RoHS konform
ja



Betriebstemp.
-55 ... 260 °C