



**Reference:** EN 2267-009D 090P (DRD 8)

### CONTACT

Market information  
 industryprojects.business@lynxéogroup.com

**International Designation:** DRD 8 090

**Designed for general Purpose Aircraft Wiring Applications.**

Multicores DRA

### STANDARDS

**Producto** EN 2267-009

**Ensayo** prEN 3475

### DESIGN CONSTRUCTION

#### CORES

2, 3 or 4 cores EN2267-009A

### IDENTIFICATION

Colours of cores : See table in this datasheet

Colours of marking: White for red and green core, green for blue and yellow cores

Marking : EN DRA \*\* FR F ++

DRA = short designation

\*\* = AWG

FR = Country of origin (FR = France)

F = Manufacturer (F = Lynxéo)

++ = Year of production (i.e. 14 = 2014)

## CHARACTERISTICS

### Características de construcción

Color	P
Type of conductor	-
Core identification	Red, Blue, Yellow, Green
Number of conductors	-
Size code	-

### Características dimensionales

Diámetro exterior máximo	10,56 mm
Diámetro exterior nominal	10,38 mm
Número de conductores	4
Maximum weight	370,8 g/m



No propagación de la llama  
 FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Resistencia a aceites  
 Very good resistance to aircraft fluids



Acorde con normativa RoHS  
 Si



Temp. ambiente de utilización  
 -55 ... 260 °C

### Características dimensionales

Nominal weight 358,26 g/m

### Características eléctricas

Maximal operating frequency 0,002 MHz

Maximum DC resistance at 20°C 2,37 Ohm/100m

Tensión de operación 600 V

### Características de uso

No propagación de la llama FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)

Resistencia a aceites Very good resistance to aircraft fluids

Arc tracking resistant Yes

Acorde con normativa RoHS Si

Temperatura ambiente de utilización (rango) -55 ... 260 °C

## IDENTIFICATION

Colours of cores : See table in this datasheet  
 Colours of marking : White for red and green core, green for blue and yellow cores  
 Marking : EN DRA \*\* FR F ++  
 DRA = short designation  
 \*\* = AWG  
 FR = Country of origin (FR = France)  
 F = Manufacturer (F = Lynxéo)  
 ++ = Year of production (i.e. 14 = 2014)



No propagación de la llama  
 FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Resistencia a aceites  
 Very good resistance to aircraft fluids



Acorde con normativa RoHS  
 Si



Temp. ambiente de utilización  
 -55 ... 260 °C