



**Reference:** EN 2714-013B 002F  
(MLB24)

**Country Ref.:** 10066389

### CONTACT

Market information  
industryprojects.business@lynx<sup>eo</sup>  
ogroup.com

**International Designation:** MLB 24 002

**Designed for general Purpose Aircraft Wiring Applications.**

260°C, Screened and Jacketed,  
Light Weight, UV cable,  
Arc tracking Resistant

### STANDARDS

**Product** EN 2267-009; EN 2714-013

### DESIGN CONSTRUCTION

#### CORES

1 cores  
EN2267-009A

#### SCREEN

Nickel plated copper spiral screen

#### JACKET

Polyimide tape  
UV PTFE tape

#### CORES

2, 3 or 4 cores  
EN2267-009A

#### SCREEN

Nickel plated copper spiral screen

#### JACKET

Polyimide tape  
UV PTFE tap

### IDENTIFICATION

#### IDENTIFICATION

1 core (MLB) : white except code 001: Light Yellow/ code 004: Light Green

Marking : EN DRA ++ FRF \*\*

Colour of marking: White for red and green core,  
Green for blue and yellow core

#### Jacket

Colour : White except code 002, 006, 012 : Light Blue

Marking : EN xxx ++ FRF \*\*

Colour of marking: Green

xxx : Short designation (MLA, MLB, MLC, MLD)

++ : AWG

FR : Country of Origin (FR = France)

F : Manufacturer (F = Lynx<sup>eo</sup>)

\*\* : Year of manufacturing (ie 14 = 2014)



Oil resistance  
Very good resistance to aircraft fluids



RoHS compliant  
Yes



Operating temp.  
-55 ... 260 °C

## CHARACTERISTICS

### Construction characteristics

Colour	-
Core identification	Red, Blue
Jacket color	Light blue
Jacket material	Polyimide tape, UV PTFE tape
Number of conductors	2
Screen	Nickel plated copper spiral screen
Sheath colour	-

### Dimensional characteristics

Nominal outer diameter	2.27 inches
Maximum outer diameter	2.4 mm
Conductor cross-section (AWG/KCMIL)	24
Number of cores	2
Screen strands nominal diameter	0.08 mm
Maximum weight	10.23 g/m
Nominal weight	9.58 g/m

### Electrical characteristics

Maximal operating frequency	0.002 MHz
Maximum DC resistance at 20°C	117 Ohm/100m
Operating Voltage Vo DC	28 V
Operating voltage between phases	200 V
Operating voltage between phase and neutral	115 V

### Usage characteristics

Oil resistance	Very good resistance to aircraft fluids
Arc tracking resistant	Yes
RoHS compliant	Yes
Operating temperature, range	-55 ... 260 °C



Oil resistance  
Very good resistance to aircraft fluids



RoHS compliant  
Yes



Operating temp.  
-55 ... 260 °C

**NEW FREE SECTION - 103114**