



Reference: Etude 133501
Country Ref.: Etude 133501

CONTACT

Market information
 industryprojects.business@lynx^{eo}
 ogroup.com

International Designation:
 70 channels 40 AWG coax cable

Ultrasound cable assemblies

STANDARDS

Product Nexans specification

Characteristics

Very flexible cable with an extremely good mechanical behaviour.
 Withstands miscellaneous sterilisation processes.

CONSTRUCTION

1- CORE (A)

AWG 40 stranded silver plated copper alloy.
 Fluoropolymer insulation.
 Diameter : 0.41 +/- 0.02 mm

AWG 48 silver plated copper helicoidal screen
 Nominal diameter : 0.47 mm

Fluoropolymer jacket
 Diameter : 0.53 +/- 0.02 mm

2- CORE (B)

8 Cores (A) twisted.
 Nominal diameter : 1.68 mm

3- CORE (C)

3 Cores (A) twisted.
 Nominal diameter : 1.14 mm

ASSEMBLY

Center : 1 Core (B) + 2 Cores (C) twisted.
 Around : 7 Cores (B) twisted.
 Nominal diameter : 5.5 mm

4- PTFE Tape

Nominal diameter : 5.63 mm

5- SHIELD

AWG 40 Tin plated copper braid.
 90% coverage.
 Nominal diameter : 5.99 mm

6- JACKET

Medical PVC
 Nom. diameter : 7.20 mm
 Max. diameter : 7.50 mm



Flessibilità del cavo
Flessibile



Temperatura operativa massima
80 °C



Temperatura operativa minima
-30 °C



Conforme RoHS (2002/95/CE)
SI

Mechanical performances

Minimum static bending radius : 5 x Overall diameter.

CHARACTERISTICS**Caratteristiche costruttive**

Costruzione	Shielded and sheathed
Forma del conduttore	Multi stranded
Materiale del conduttore	Rame rivestito in argento
Isolamento	FEP

Caratteristiche dimensionali

Diametro esterno	7,2 mm
Peso approssimativo	71 g/m

Caratteristiche elettriche

Tensione operativa	24 V
--------------------	------

Caratteristiche meccaniche

Flessibilita' del cavo	Flessibile
------------------------	------------

Caratteristiche d'utilizzo

Temperatura operativa massima	80 °C
Temperatura operativa minima	-30 °C
Conforme RoHS (2002/95/CE)	Si