



Reference: Etude 133502
Country Ref.: Etude 133502

CONTACT

Market information
 industryprojects.business@lynx^{eo}
 ogroup.com

International Designation:

134 channels 40 AWG coax cable

Ultrasound cable assemblies

STANDARDS

Producto Especificaciones Nexans

Characteristics

Very flexible cable with an extremely good mechanical behaviour.
 Withstands miscellaneous sterilisation processes.

CONSTRUCTION

1- CORE (A)

AWG 40 stranded silver plated copper alloy.
 Fluoropolymer insulation.
 Diameter : 0.26 +/- 0.03 mm

AWG 48 silver plated copper helicoidal screen
 Nominal diameter : 0.32 mm

Fluoropolymer jacket
 Diameter : 0.39 +/- 0.03 mm

2- CORE (B)

6 Cores (A) twisted.
 Nominal diameter : 1.16 mm

3- CORE (C)

8 Cores (A) twisted.
 Nominal diameter : 1.24 mm

ASSEMBLY

Center : 1 Core (B) + 5 Cores (C) twisted.
 Around : 11 Cores (C) twisted.
 Nominal diameter : 5.5 mm

4- PTFE Tape

Nominal diameter : 5.57 mm

5- SHIELD

AWG 40 Tin plated copper braid.
 90% coverage.
 Nominal diameter : 5.83 mm

6- JACKET

Medical PVC
 Nom. diameter : 7.20 mm
 Max. diameter : 7.50 mm



Flexibilidad del cable
Flexible



Temperatura máxima operativa
 80 °C



Temperatura mínima operativa
 -30 °C



Acorde con normativa RoHS
 Si

Mechanical performances

Minimum static bending radius : 5 x Overall diameter.

CHARACTERISTICS**Características de construcción**

Construction type	Shielded and sheathed
Forma del conductor	Cableado flexible
Material del conductor	Silver coated copper
Aislamiento	Fluor polymer

Características dimensionales

Approximate weight	87 g/m
Diámetro exterior	7,2 mm

Características eléctricas

Tensión de operación	24 V
----------------------	------

Características mecánicas

Flexibilidad del cable	Flexible
------------------------	----------

Características de uso

Temperatura máxima operativa	80 °C
Temperatura mínima operativa	-30 °C
Acorde con normativa RoHs	Si