



- Instrumentation cables 170/300 V
- Overall Screen (OS)
- Oil resistant

STANDARDS

Test IEC 60331; IEC 60332-3-22 Cat. A

APPLICATIONS

These instrumentation and communication cable are used to transmit analogue or digital signals in measurement and process control where chemicals may be present. They maintain circuit integrity when exposed to fire

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

Design

Conductor:

Stranded bare copper class 2

Insulation:

Silicone rubber (SIL)

Overall screen:

Polyester tape

Tinned copper drain wire,

Copper backed polyester tape

Outer sheath:

Polyvinyl chloride (PVC)

Colour: black

Other colour on request.

Core identification

Pair: white - black

Quad: white - black - red - blue (2 pair cables assembled as a quad)

White core printed with pair number

Marking

NEXANS 279 SIL/OA.SCR/PVC 170/300V Nber of pairs & cross-section Cu IEC 60331
IEC 60332-3-22 (A) MM YYYY Manufacturing number + metric marking

Standards

EN 50288-7 (Design guide-lines)



额定电压 U_0/U
170/300V



耐火
IEC 60331



阻燃
EN IEC 60332-3-22
(cat A)



耐油
是



抗电磁干扰
是



操作温度
-20 ... 60 ° C



芯线最高静止温度
90 ° C

CHARACTERISTICS

结构特性

导体材料	裸铜线
导体类型	Stranded, class 2
绝缘	硅树脂橡胶
总屏蔽	Tinned copper drain wire + copper polyester tape
外护套	聚氯乙烯
防护	no

尺寸特性

线对数	10
导线截面	0.75 mm ²
导线直径	1.1 mm
绝缘外径	2.26 mm
外径最小值	17.6 mm
Maximum outer diameter	20.6 mm
近似重量	380 kg/km

电气特性

额定电压U ₀ /U	170/300V
-----------------------	----------

使用特性

耐火	IEC 60331
阻燃	EN IEC 60332-3-22 (cat A)
耐油	是
抗电磁干扰	是
操作温度范围	-20 ... 60 ° C
芯线最高静止温度	90 ° C
标准	EN

SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

Tinned copper conductors available on request



额定电压U₀/U
170/300V



耐火
IEC 60331



阻燃
EN IEC 60332-3-22
(cat A)



耐油
是



抗电磁干扰
是



操作温度
-20 ... 60 ° C



芯线最高静止温度
90 ° C