



- Instrumentation cables 170/300 V
- Individual & Overall Screen (IOS)
- Oil resistant

STANDARDS

Test IEC 60331; IEC 60332-3-22 Cat. A

APPLICATIONS

These instrumentation and communication cable are used to transmit analogue or digital signals in measurement and process control where chemicals may be present. The individual screening of each pair limits the consequence of crosstalk. They maintain circuit integrity when exposed to fire.

Design

Conductor:

Stranded bare copper class 2

Insulation:

Silicone rubber (Sil)

Individual screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

Polyester tape

Overall screen:

Polyester tape

Tinned copper drain wire

Copper backed polyester tape

Outer sheath:

Polyvinyl chloride (PVC)

Colour: black

Other colour on request.

Core identification

Pair: white - black

White core printed with pair number



额定电压 U_0/U
170/300V



耐火
IEC 60331



阻油
IEC 60332-3-22 (A)



耐油



抗电磁干扰



操作温度



芯线最高停止温度

Marking

NEXANS 279 SIL/IND.+0A.SCR/PVC.170/300V Nber. of pairs & cross-section Cu IEC
60331 IEC-60332-3-22 (A) MM YYYY Manufacturing numbers+ metric marking

Standards

EN 50288-7 (Design guide-lines)

CHARACTERISTICS

结构特性

导体材料	裸铜线
导体类型	Stranded, class 2
绝缘	硅树脂橡胶
线对屏蔽	Tinned copper drain wire + aluminium/polyester tape
总屏蔽	Tinned copper drain wire + copper polyester tape
外护套	聚氯乙烯
防护	no

尺寸特性

线对数	2
导线截面	2.5 mm ²
导线直径	1.91 mm
绝缘外径	3.07 mm
外径最小值	14.1 mm
Maximum outer diameter	16.4 mm
近似重量	268 kg/km

电气特性

额定电压U ₀ /U	170/300V
-----------------------	----------

使用特性

耐火	IEC 60331
阻燃	EN IEC 60332-3-22 (cat A)
耐油	是
抗电磁干扰	是
操作温度范围	-20 ... 60 ° C
芯线最高静止温度	90 ° C
标准	EN

SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

Tinned copper conductors available on request



额定电压U₀/U
170/300V



耐火
IEC 60331



阻燃
EN IEC 60332-3-22
(cat A)



耐油
是



抗电磁干扰
是



操作温度
-20 ... 60 ° C



芯线最高静止温度
90 ° C