



- Instrumentation cables 170/300 V
- Individual & Overall Screen (IOS)
- **Oil resistant**

STANDARDS

Tests IEC 60331; IEC 60332-3-22 Cat.A

APPLICATIONS

These instrumentation and communication cable are used to **transmit analogue or digital signals in measurement and process control where chemicals may be present. The individual screening of each pair limits the consequence of crosstalk. They maintain circuit integrity when exposed to fire.**

Design

Conductor:

Stranded bare copper class 2

Insulation:

Silicone rubber (Sil)

Individual screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

Polyester tape

Overall screen:

Polyester tape

Tinned copper drain wire

Copper backed polyester tape

Outer sheath:

Polyvinyl chloride (PVC)

Colour: black

Other colour on request.

Core identification

Pair: white - black

White core printed with pair number



Nennspannung Uo/U
170/300V



Feuerbeständig
IEC 60331



Marking



EXANS 279 SILIND OA.SCR/PVC 170/300V No. of pairs & cross section Cu IEC
60331 IEC 60332-3-22(A) MM YYYY Manufacturing number + metric marking
(cat A) Ja

Standards

EN 50288-7 (Design guide-lines)

Alle Zeichnungen, Entwürfe, Spezifikationen, Pläne und Angaben zu Gewichten, Größen und Abmessungen in der technischen oder kommerziellen Dokumentation von Lynx^{eo} sind nur indikativ und sind für Lynx^{eo} nicht verbindlich und dürfen nicht als Zusicherung seitens Lynx^{eo} betrachtet werden

CONTACT

Market information
industryprojects.business@lynx^{eo}.com
ogroup.com

CHARACTERISTICS

Konstruktionsmerkmale

Leitermaterial	Kupfer, blank
Leitertyp	Stranded, class 2
Isolierung	Silicone rubber
Einzel geschirmt	Tinned copper drain wire + aluminium/polyester tape
Gemeinsamer Schirm	Tinned copper drain wire + copper polyester tape
Außenmantel	PVC
Schutz	Nein

Abmessungsmerkmale

Anzahl Paare	30
Leiterquerschnitt	2,5 mm ²
Leiterdurchmesser	1,91 mm
Durchmesser über Isolierung	3,07 mm
Außendurchmesser Mindestwert	37,5 mm
Maximaler Außendurchmesser	43,8 mm
Nettogewicht ca.	2425 kg/km

Elektrische Eigenschaften

Nennspannung U ₀ /U	170/300V
--------------------------------	----------

Anwendungsmerkmale

Feuerbeständig	IEC 60331
Flammwidrig	EN IEC 60332-3-22 (cat A)
Ölbeständig	Ja
Elektromagnetisch geschirmt	Ja
Betriebstemperatur	-20 ... 60 °C
Max. Betriebstemperatur am Leiter	90 °C
Standard	EN

SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

Tinned copper conductors available on request



Nennspannung U₀/U
170/300V



Feuerbeständig
IEC 60331



Flammwidrig
EN IEC 60332-3-22
(cat A)



Ölbeständig
Ja



Elektromagnetisch
geschirmt
Ja



Betriebstemp.
-20 ... 60 °C



Max. Betriebstemp. am
Leiter
90 °C