



- Instrumentation cables 250 V
- Individual & Overall Screen (IOS)
- **Hydrocarbons resistant**

STANDARDS

Tests IEC 60332-3-22 Cat.A

APPLICATIONS

These instrumentation and communication cable are used to **transmit analogue or digital signals in measurement and process control where chemicals may be present. The individual screening of each pair limits the consequence of crosstalk.**

CONTACT

Market information
industryprojects.business@lynxéogroup.com

Nexans code

- 1st serie = number of pairs, triples or quads: 01 to 27
- 2nd serie = pair (IP), triple (IT), quad (IQ)
- 3rd serie = conductor 05 (1 x 0.8 mm), 09 (7 x 0.4 mm) or 15 (7 x 0.52 mm)
- 4th serie = overall screen (EG), individual screen + overall screen (EI)
- 5th serie = mechanical protection: without metal tape (SF), with steel tape (FA), with lead and steel tape (PF)

Design

Conductor:

- Solid plain copper 0.50 mm² (1 x 0.80 mm) or stranded plain copper cross-section 0.88 mm² (7 x 0.40 mm)

Insulation:

- Polyvinyl chloride (PVC)

Individual screen:

- Polyester tape
- Tinned copper drain wire
- Aluminium/polyester tape

Individual sheath:

- Polyvinyl chloride (PVC)

Collective screen:

- Polyester tape
- Tinned copper drain wire
- Aluminium/polyester tape

Outer sheath:

- Polyvinyl chloride (PVC)
- Colour: light-blue or grey

Core identification

Pair: natural - red
 Triple: natural - red - blue
 Blue individual sheath printed with pair or triple number

Marking

NEXANS 279 - Number of pair/triples IP/IT-05/09 EI SF IEC 60332-3-22(A) + metric marking



Flammwidrig
 EN IEC 60332-3-22 (cat A)



Chemische Beständigkeit
 Hydrocarbons resistant



Elektromagnetisch geschirmt
 Ja



Betriebstemp.
 -20 ... 60 °C



Max. Betriebstemp. am Leiter
 70 °C

CHARACTERISTICS

Konstruktionsmerkmale

Leitermaterial	blank
Isolierung	PVC
Einzeln geschirmt	Tinned copper drain wire + aluminium/polyester tape
Individual sheath	PVC
Gemeinsamer Schirm	Tinned copper drain wire + aluminium/polyester tape
Außenmantel	PVC

Abmessungsmerkmale

Leiterquerschnitt	0,5 mm ²
Anzahl Paare	27
Anzahl der Dreier	-
Leiterdurchmesser	0,8 mm
Durchmesser über Isolierung	1,6 mm
Außendurchmesser Mindestwert	29,3 mm
Maximaler Außendurchmesser	33,6 mm
Nettogewicht ca.	1145 kg/km

Elektrische Eigenschaften

Betriebsspannung	250 V
------------------	-------

Anwendungsmerkmale

Flammwidrig	EN IEC 60332-3-22 (cat A)
Chemische Beständigkeit	Hydrocarbons resistant
Elektromagnetisch geschirmt	Ja
Betriebstemperatur	-20 ... 60 °C
Max. Betriebstemperatur am Leiter	70 °C
Standard	NFM



Flammwidrig
EN IEC 60332-3-22 (cat A)



Chemische Beständigkeit
Hydrocarbons resistant



Elektromagnetisch geschirmt
Ja



Betriebstemp.
-20 ... 60 °C



Max. Betriebstemp. am Leiter
70 °C

ELECTRICAL DATA NF M 87202

Electrical data

Section	Maximum Voltage (V)	Voltage Test (V)	DC Lineic resistance at 20°C (Ω/km)	Self Inductance mH/km		Capacitance between cond. (nF/km)
				Non Armoured	Armoured	
05	250	2 000	37.5	0.33	0.38	≤145
09	250	2 000	21.4	0.31	0.36	≤160
15	250	2 000	12.1	0.31	0.36	≤180

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

10 x outer diameter

To be doubled during laying operations



Flammwidrig
EN IEC 60332-3-22 (cat A)



Chemische Beständigkeit
Hydrocarbons resistant



Elektromagnetisch geschirmt
Ja



Betriebstemp.
-20 ... 60 °C



Max. Betriebstemp. am Leiter
70 °C