



- Instrumentation cables 250 V
- Individual & Overall Screen (IOS)
- **Hydrocarbons resistant**

### STANDARDS

Test IEC 60332-3-22 Cat.A

### APPLICATIONS

These instrumentation and communication cable are used to **transmit analogue or digital signals in measurement and process control where chemicals may be present. The individual screening of each pair limits the consequence of crosstalk.**

### CONTACT

Market information  
industryprojects.business@lynx<sup>eo</sup>.com  
ogroup.com

### Nexans code

- 1st serie = number of pairs, triples or quads: 01 to 27
- 2nd serie = pair (IP), triple (IT), quad (IQ)
- 3rd serie = conductor 05 (1 x 0.8 mm), 09 (7 x 0.4 mm) or 15 (7 x 0.52 mm)
- 4th serie = overall screen (EG), individual screen + overall screen (EI)
- 5th serie = mechanical protection: without metal tape (SF), with steel tape (FA), with lead and steel tape (PF)

### Design

#### Conductor:

- Solid plain copper 0.50 mm<sup>2</sup> (1 x 0.80 mm) or stranded plain copper cross-section 0.88 mm<sup>2</sup> (7 x 0.40 mm)

#### Insulation:

- Polyvinyl chloride (PVC)

#### Individual screen:

- Polyester tape
- Tinned copper drain wire
- Aluminium/polyester tape

#### Individual sheath:

- Polyvinyl chloride (PVC)

#### Collective screen:

- Polyester tape
- Tinned copper drain wire
- Aluminium/polyester tape

#### Outer sheath:

- Polyvinyl chloride (PVC)
- Colour: light-blue or grey

### Core identification

Pair: natural - red

Triple: natural - red - blue

Blue individual sheath printed with pair or triple number

### Marking

NEXANS 279 - Number of pair/triples IP/IT 05/09 EI SF IEC 60332-3-22(A) + metric marking



Fuoco ritardante  
EN IEC 60332-3-22 (cat A)



Resistenza chimica  
Resistente agli idrocarburi



Resistenza ad interferenza elettromagnetica  
SI



Temperatura Operativa  
-20 ... 60 °C



Temp. max di servizio del conduttore  
70 °C

**CHARACTERISTICS****Caratteristiche costruttive**

Materiale del conduttore	Rame nudo
Isolamento	PVC
Schermo Individuale	Filo di drenaggio in rame stagnato + nastro di alluminio/ poliestere
Guaina singola	PVC
Schermo Collettivo	Filo di rame stagnato + Nastro Alluminio / Poliestere
Guaina esterna	PVC

**Caratteristiche dimensionali**

Sezione del conduttore del cavo	0,88 mm <sup>2</sup>
Numero di coppie	7
Numero di terne	-
Diametro nominale del conduttore del cavo	1,2 mm
Diametro nominale sull'isolante	2,2 mm
Diametro esterno min	18,9 mm
Diametro esterno max	21,7 mm
Peso approssimativo del cavo	485 kg/km

**Caratteristiche elettriche**

Tensione operativa	250 V
--------------------	-------

**Caratteristiche d'utilizzo**

Fuoco ritardante	EN IEC 60332-3-22 (cat A)
Resistenza chimica	Resistente agli idrocarburi
Resistenza ad interferenza elettromagnetica	Si
Temperatura Operativa	-20 ... 60 °C
Temperatura massima di servizio del conduttore	70 °C
Standard	NFM



Fuoco ritardante  
EN IEC 60332-3-22 (cat A)



Resistenza chimica  
Resistente agli idrocarburi



Resistenza ad interferenza elettromagnetica  
Si



Temperatura Operativa  
-20 ... 60 °C



Temp. max di servizio del conduttore  
70 °C

**ELECTRICAL DATA NF M 87202****Electrical data**

Section	Maximum Voltage (V)	Voltage Test (V)	DC Lineic resistance at 20°C ( $\Omega$ /km)	Self Inductance mH/km		Capacitance between cond. (nF/km)
				Non Armoured	Armoured	
05	250	2 000	37.5	0.33	0.38	$\leq 145$
09	250	2 000	21.4	0.31	0.36	$\leq 160$
15	250	2 000	12.1	0.31	0.36	$\leq 180$

**SELLING AND DELIVERY INFORMATION**

Minimum bending radius:

10 x outer diameter

To be doubled during laying operations



Fuoco ritardante  
EN IEC 60332-3-22 (cat A)



Resistenza chimica  
Resistente agli idrocarburi



Resistenza ad interferenza elettromagnetica  
SI



Temperatura Operativa  
-20 ... 60 °C



Temp. max di servizio del conduttore  
70 °C