



- Instrumentation cables 250 V
- Individual & Overall Screen (IOS)
- **Hydrocarbons resistant**

### STANDARDS

Ensayo IEC 60332-3-22 Cat.A

### APPLICATIONS

These instrumentation and communication cable are used to **transmit analogue or digital signals in measurement and process control where chemicals may be present. The individual screening of each pair limits the consequence of crosstalk.**

### CONTACT

Market information  
industryprojects.business@lynxegroup.com

### Nexans code

- 1st serie = number of pairs, triples or quads: 01 to 27
- 2nd serie = pair (IP), triple (IT), quad (IQ)
- 3rd serie = conductor 05 (1 x 0.8 mm), 09 (7 x 0.4 mm) or 15 (7 x 0.52 mm)
- 4th serie = overall screen (EG), individual screen + overall screen (EI)
- 5th serie = mechanical protection: without metal tape (SF), with steel tape (FA), with lead and steel tape (PF)

### Design

#### Conductor:

- Solid plain copper 0.50 mm<sup>2</sup> (1 x 0.80 mm) or stranded plain copper cross-section 0.88 mm<sup>2</sup> (7 x 0.40 mm)

#### Insulation:

- Polyvinyl chloride (PVC)

#### Individual screen:

- Polyester tape
- Tinned copper drain wire
- Aluminium/polyester tape

#### Individual sheath:

- Polyvinyl chloride (PVC)

#### Collective screen:

- Polyester tape
- Tinned copper drain wire
- Aluminium/polyester tape

#### Outer sheath:

- Polyvinyl chloride (PVC)
- Colour: light-blue or grey

### Core identification

Pair: natural - red

Triple: natural - red - blue

Blue individual sheath printed with pair or triple number

### Marking

NEXANS 279 - Number of pair/triples IP/IT 05/09 EI SF IEC 60332-3-22(A) + metric marking



No propagador del incendio  
EN IEC 60332-3-22 (cat A)



Resistencia química  
Hydrocarbons resistant



Resistencia a interferencias electromagnéticas  
Sí



Temp. ambiente de utilización  
-20 ... 60 °C



Max.conductor temp.in service  
70 °C

## CHARACTERISTICS

### Características de construcción

Material del conductor	Plain copper
Aislamiento	PVC
Individual screen	Tinned copper drain wire + aluminium/polyester tape
Individual sheath	PVC
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Cubierta exterior	PVC

### Características dimensionales

Sección del conductor	0,88 mm <sup>2</sup>
Número de pares	12
Number of triples	-
Diámetro del conductor	1,2 mm
Diámetro sobre aislamiento	2,2 mm
Diámetro exterior mínimo	24,7 mm
Diámetro exterior máximo	28,3 mm
Peso aproximado	830 kg/km

### Características eléctricas

Tensión de operación	250 V
----------------------	-------

### Características de uso

No propagador del incendio	EN IEC 60332-3-22 (cat A)
Resistencia química	Hydrocarbons resistant
Resistencia a interferencias electromagnéticas	Sí
Temperatura ambiente de utilización (rango)	-20 ... 60 °C
Temperatura máxima del conductor	70 °C
Standard	NFM



No propagador del incendio  
EN IEC 60332-3-22 (cat A)



Resistencia química  
Hydrocarbons resistant



Resistencia a interferencias electromagnéticas  
Sí



Temp. ambiente de utilización  
-20 ... 60 °C



Max. conductor temp.in service  
70 °C

## ELECTRICAL DATA NF M 87202

### Electrical data

Section	Maximum Voltage (V)	Voltage Test (V)	DC Lineic resistance at 20°C (Ω/km)	Self Inductance mH/km		Capacitance between cond. (nF/km)
				Non Armoured	Armoured	
05	250	2 000	37.5	0.33	0.38	≤145
09	250	2 000	21.4	0.31	0.36	≤160
15	250	2 000	12.1	0.31	0.36	≤180

## SELLING AND DELIVERY INFORMATION

Minimum bending radius:

10 x outer diameter

To be doubled during laying operations



No propagador del incendio  
EN IEC 60332-3-22 (cat A)



Resistencia química  
Hydrocarbons resistant



Resistencia a interferencias electromagnéticas  
Sí



Temp. ambiente de utilización  
-20 ... 60 °C



Max.conductor temp.in service  
70 °C