



- Instrumentation cables 250 V
- Individual & Overall Screen (IOS)
- **Hydrocarbons resistant and enhanced resistance to aromatics**

STANDARDS

Ensayo IEC 60332-3-22 Cat.A

APPLICATIONS

These instrumentation and communication cables are used to **transmit analogue or digital signals in measurement and process control**. They are well adapted to **underground use** in industrial applications, in moist areas, where **chemical and mechanical protection are needed**. The **lead cover brings an enhanced resistance to aromatics hydrocarbons**. The **individual screening of each pair limits the consequence of crosstalk**.

Nexans code

- 1st serie = number of pairs, triples or quads: 01 to 27
- 2nd serie = pair (IP), triple (IT), quad (IQ) - 3rd serie = conductor 05 (1 x 0.8 mm), 09 (7 x 0.4 mm) or 15 (7 x 0.52 mm)
- 4th serie = overall screen (EG), individual screen + overall screen (EI)
- 5th serie = mechanical protection: without metal tape (SF), with steel tape (FA), with lead and steel tape (PF)

Design

Conductor:

- Solid plain copper 0.50 mm² (1 x 0.80 mm) or stranded plain copper cross-section 0.88 mm² (7 x 0.40 mm)

Insulation:

- Polyvinyl chloride (PVC)

Individual screen:

- Polyester tape
- Tinned copper drain wire
- Aluminium/polyester tape

Individual sheath:

- Polyvinyl chloride (PVC)

Overall screen:

- Polyester tape
- Tinned copper drain wire
- Aluminium/polyester tape

Inner sheath:

- Polyvinyl chloride (PVC)

Lead covering

Armour:

- Paraffin-waxed crepe paper
- Double steel tape

Outer sheath:

- Polyvinyl chloride (PVC)
- Colour: light-blue or grey

CONTACT

Market information
industryprojects.business@lynxéogroup.com



No propagador del incendio
EN IEC 60332-3-22 (cat A)



Resistencia química
Hydrocarbons resistant and enhanced resistances to aromatics



Resistencia a interferencias electromagnéticas
SI



Temp. ambiente de utilización
-20 ... 60 °C



Max. conductor temp.in service
70 °C

Core identification

Pair: natural - red
Triple: natural - red blue
Double individual sheath printed with pair/triple number

Marking

NEXANS 279- Number of pair/triple IP/IT 05/09 EI PF IEC 60332-3-22(A)+ metric marking

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Lynxéo is indicative only and shall not be binding on Lynxéo or be treated as constituting a representation on the part of Lynxéo.

CHARACTERISTICS

Características de construcción

Material del conductor	Plain copper
Aislamiento	PVC
Individual screen	Tinned copper drain wire + aluminium/polyester tape
Individual sheath	PVC
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Cubierta interior	PVC
Lead Sheath	Yes
Tipo de armadura	Cintas de acero
Cubierta exterior	PVC

Características dimensionales

Sección del conductor	0,88 mm ²
Número de pares	27
Number of triples	-
Diámetro del conductor	1,2 mm
Diámetro sobre aislamiento	2,2 mm
Diameter over inner sheath	36,3 mm
Lead cover diameter	39.9 mm
Diameter over armour	41,7 mm
Diámetro exterior mínimo	43,9 mm
Diámetro exterior máximo	48,5 mm
Peso aproximado	4500 kg/km

Características eléctricas

Tensión de operación	250 V
----------------------	-------

Características de uso

No propagador del incendio	EN IEC 60332-3-22 (cat A)
Resistencia química	Hydrocarbons resistant and enhanced resistances to aromatics
Resistencia a interferencias electromagnéticas	Sí
Temperatura ambiente de utilización (rango)	-20 ... 60 °C
Temperatura máxima del conductor	70 °C
Standard	NFM



No propagador del incendio
 EN IEC 60332-3-22 (cat A)



Resistencia química
 Hydrocarbons resistant and enhanced resistances to aromatics



Resistencia a interferencias electromagnéticas
 Sí



Temp. ambiente de utilización
 -20 ... 60 °C



Max. conductor temp. in service
 70 °C

ELECTRICAL DATA NF M 87202

Electrical data

Section	Maximum Voltage (V)	Voltage Test (V)	DC Lineic resistance at 20°C (Ω/km)	Self Inductance mH/km		Capacitance between cond. (nF/km)
				Non Armoured	Armoured	
05	250	2 000	37.5	0.33	0.38	≤145
09	250	2 000	21.4	0.31	0.36	≤160
15	250	2 000	12.1	0.31	0.36	≤180

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

- 10 x outer diameter
- To be doubled during laying operations



No propagador del incendio
EN IEC 60332-3-22 (cat A)



Resistencia química
Hydrocarbons resistant and enhanced resistances to aromatics



Resistencia a interferencias electromagnéticas
Sí



Temp. ambiente de utilización
-20 ... 60 °C



Max.conductor temp.in service
70 °C