



### CONTACT

Market information  
 industryprojects.business@lynx<sup>eo</sup>.com  
 lynx<sup>eo</sup>.com

- Low voltage cables 0.6/1 (1.2) V
- CST 74C068
- Zero halogen (SH)
- **Cables installed inside of the containment area (K1)**
- Unarmoured (NA)

### STANDARDS

**Product** IEC 60228

**Test** IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

### APPLICATIONS

These low voltage cables are used for lighting system power supply, engine power supply and solenoid valve power supply.

### DESIGN

#### Design

##### Conductor:

Stranded bare copper or aluminium (class 2)

##### Insulation:

Cross-linked halogen free (SH)

##### Covering (optional):

Halogen free

##### Outer sheath:

Low smoke, zero halogen (LSZH)

Colour: Blue

### Core identification

According to HD308 S2

### Marking

LYNXEO 279 Nber of cores & cross-section Cu/Al CST 74 C 068 00 K1 SH 0.6/1 (1.2) kV YYYY Manufacturing number + metric marking

### STANDARD



Halogen free  
 IEC 60754-1



Rated Voltage U<sub>0</sub>/U<sub>i</sub>  
 (Um)  
 0.6/1 (1.2) kV



Fire retardant  
 NF C 32070 C1;  
 IEC 60332-3-23  
 (cat. B)  
 Standard  
 IEC 60332-3-23(B)  
 Smoke density  
 EN/IEC 61034-2



Radiation resistant  
 Yes



LOCA  
 Yes



Life cycle 60years  
 Yes



Max. conductor  
 temp. in service  
 90 °C

### CHARACTERISTICS

#### Construction characteristics

Conductor material	Plain copper
Type of conductor	Stranded, class 2
Insulation	Halogen-free
Outer sheath	Halogen-free
Halogen free	IEC 60754-1

#### Dimensional characteristics

Conductor cross-section	50 mm <sup>2</sup>
Number of cores	2
Conductor diameter	8.2 mm
Diameter over insulation	10.2 mm
Minimum outer diameter	25.2 mm
Maximum outer diameter	27.8 mm
Approximate weight	1550 kg/km

#### Electrical characteristics

Rated Voltage U <sub>o</sub> /U (Um)	0.6/ 1 (1.2) kV
--------------------------------------	-----------------

#### Usage characteristics

Fire retardant	NF C 32070 C1; IEC 60332-3-24 (cat.B)
Smoke density	EN/IEC 61034-2
Radiation resistant	Yes
Loss of coolant accident resistant	Yes
Life cycle 60years	Yes
Max. conductor temperature in service	90 °C
Operating temperature, range	-20 ... 60 °C
Nuclear Classification	Class 1 E LOCA /K1

### SELLING AND DELIVERY INFORMATION

Minimum bending radius:

8 x outer diameter  
To be doubled during laying operations



Halogen free  
IEC 60754-1



Rated Voltage U<sub>o</sub>/U (Um)  
0.6/ 1 (1.2) kV



Fire retardant  
NF C 32070 C1;  
IEC 60332-3-24  
(cat.B)



Smoke density  
EN/IEC 61034-2



Radiation resistant  
Yes



LOCA  
Yes



Life cycle 60years  
Yes



Max. conductor temp. in service  
90 °C