



CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

- Low voltage cables 0.6/1 (1.2) V
- CST 74C068
- Zero halogen (SH)
- Cables installed inside of the containment area (K1)
- Unarmoured (NA)

STANDARDS

Product IEC 60228

Test IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

APPLICATIONS

These low voltage cables are used for lighting system power supply, engine power supply and solenoid valve power supply.

DESIGN

Design

Conductor:

Stranded bare copper or aluminium (class 2)

Insulation:

Cross-linked halogen free (SH)

Covering (optional):

Halogen free

Outer sheath:

Low smoke, zero halogen (LSZH)

Colour: Blue

Core identification

According to HD308 S2

Marking

LYNXEO 279 Nber of cores & cross-section Cu/Al CST 74 C 068 00 K1 SH 0.6/1 (1.2) kV YYYY Manufacturing number + metric marking


STANDARD



无卤
IEC 60754-1



额定电压U₀/U
0.6/ 1 (1.2) kV



Standard
IEC 60332-3-23 (B)
阻燃
NF C 32-070/C1
IEC 60332-3-24
(cat. B)



耐辐射



LOCA



Life cycle
60years
是



芯线最高静止温度
90 ° C

CHARACTERISTICS

结构特性

导体材料	裸铜
导体类型	Stranded, class 2
绝缘	无卤
外护套	无卤
无卤	IEC 60754-1

尺寸特性

导线截面	240 mm ²
芯线数	2
导线直径	18.2 mm
绝缘外径	21.6 mm
外径最小值	50.6 mm
Maximum outer diameter	55.9 mm
近似重量	6979 kg/km

电气特性

额定电压U ₀ /U	0.6/ 1 (1.2) kV
-----------------------	-----------------

使用特性

阻燃	NF C 32070 C1; IEC 60332-3-24 (cat. B)
烟密度	EN/IEC 61034-2
耐辐射	Yes
Loss of coolant accident resistant	是
Life cycle 60years	是
芯线最高静止温度	90 ° C
操作温度范围	-20 ... 60 ° C
Nuclear Classification	Class 1 E LOCA /K1

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

8 x outer diameter
To be doubled during laying operations



无卤
IEC 60754-1



额定电压U₀/U
0.6/ 1 (1.2) kV



阻燃
NF C 32070 C1;
IEC 60332-3-24
(cat. B)



烟密度
EN/IEC 61034-2



耐辐射
Yes



LOCA
是



Life cycle
60years
是



芯线最高静止温度
90 ° C