

**CONTACT**

Market information  
industryprojects.business@lynxe  
ogroup.com

Flexible shielded PUR data transmission cables with UL approval

UL type CMX according to UL 444

**STANDARDS**

**Product** UL 444

**Application**

The cable WINDLINK® Data flexible C-PUR was specifically designed for wind turbines. These cable is used for data transmission where high flexibility and oil resistance are required. It is therefore a suitable connection for electrical panels and sensors.

**Product characteristics**

- Vibration resistant
- Flame retardant according to IEC 60332-1-2
- Minimum bending radius during installation
  - without load  $\geq 5 \times D$
  - with load  $\geq 10 \times D$
- Operating temperature acc. to
  - Nexans spec.:  $-40^{\circ}\text{C}$  up to  $+90^{\circ}\text{C}$
  - UL CMX:  $-40^{\circ}\text{C}$  up to  $+75^{\circ}\text{C}$
- Oil resistant according to EN 60811-2-1
- Halogen free according to IEC 60754
- UV resistant according to IEC 60068-2-5
- Ozone resistant according to EN 60811-2-1 clause 8

**Approval**

- UL 444

**Design****Conductor**

Bare copper stranded

**Insulation**

Halogen free compound

Core indication: colour code according to DIN 47100

**Assembly**

Conductors twisted in layers + polyester tape + Aluminium/polyester tape (Aluminium outside)

**Drain wire**

Tinned copper

**Shield**

Tinned copper braid, coverage  $\geq 80\%$  + non woven tape

**Sheath**

PUR compound, colour black Ral 9005

**CHARACTERISTICS****Construction characteristics**

Conductor material	-
Insulation	-
Insulation colour	-
Lay Up	-
Screen	-
Outer sheath	-
Inner sheath	-
Construction type	7 x 0.34

**Dimensional characteristics**

Conductor diameter (mm)	-
Insulation sheath thickness	- mm
Inner sheath thickness	- mm
Nominal outer sheath thickness	- mm
Diameter over braid	- mm
Maximum cable diameter	- mm
Minimum cable diameter	- mm
Approximate weight	70 kg/km
Nominal outer diameter	6.2 mm
Copper content	44.6 kg/km

**Electrical characteristics**

Rated Voltage U <sub>o</sub> /U	300/500 V
Resistance of inner conductor (DC)	- Ohm/km
Max. Electrical Resistance AC 60Hz 70°C	- Ohm/km
Max. Electrical Resistance AC 60Hz 90°C	- Ohm/km
Max. transfer impedance at 10MHz	10 mOhm/m
Inductive reactance	- Ohm/km
Operating capacitances	- mF/km
Minimum insulation resistance	100 MOhm.km
Permissible short circuit current	- kA
Operating voltage - range	- kV
Test voltage AC at 50hz conductor /conductor	1500 V
Maximum operating voltage	-
Test voltage AC at 50hz conductor/screen	1500 V
Transfer impedance	-

**Mechanical characteristics**

Tensile strength	- N
Maximum tensile load	- N
Torsion stress	- °/m
Maximum Tensile Strength Conductor	- kN

**Usage characteristics**

Gases corrosivity	-
Fire resistant	-

### Usage characteristics

Flame retardant	-
Oil resistance	-
U.V resistance	-
Ozone resistance	-
Max. conductor temperature in service	70 °C
Installation temperature, range	- °C
Short-circuit max. conductor temperature	- °C
Operating temperature, range	-40 ... 75 °C

## COMPLEMENTARY TECHNICAL DATA FOR WINDLINK® DATA FLEXIBLE C-PUR

### Electrical Properties

	0.34 mm <sup>2</sup>	0.50 mm <sup>2</sup>
Max. conductors resistance at 20°C [Ω.Km]	58	39
Max. DC resistance of overall screen [Ω/Km]	15.5	10.0

## SELLING AND DELIVERY INFORMATION

Marking e.g.

NEXANS INTERCOND - Week/Year of production - WINDLINK Li-9Y(St)C11Y n x yy mm<sup>2</sup>/AWG size - E222606 (UL)  
CMX 75°C - shielded data cable

n: number of conductors

yy: section of conductor

Meter marking