



HIGH TEMPERATURE FLEXIBLE POWER CABLES

FLAMEX® EN 50382-2 F power cables are designed and dedicated to be used on rolling stock equipment where high operating temperature is required to save cable weight. Thanks to its high flexibility, these cables with low bending radius are frequently installed on locomotive equipment.

STANDARDS

Product EN 45545-2 (HL3); EN 50382-2; IEC 60228

DESIGN

1. Conductor

Flexible class 5 copper according to IEC 60228

- tinned copper for 120°C Class
- plain copper for 150°C Class

Separator: Unweaved tape

2. Insulation

Cross-linked silicone type EI 111 according to EN 50382-1

Colour: black outer layer

Example of marking: FLAMEX SI - EN 50382-2 - Voltage rate (1800V or 3600V) - cross-section mm² - F - temperature class (120°C or 150°C) - LYNXEO 279 - week/year

CONTACT

Markets and Products Information
rollingstock.business@lynxeogroup.com

GUIDE TO USE

- Cabling rules are given in EN 50343 and EN 50355
- Permissible current carrying capacities: values and calculation method are given in EN 50343
- Bending radius:
 - Static use: 4 x outer cable diameter
 - For installation and occasional movements: 6 x outer cable diameter
- Pulling tensible force (dynamic) during installation: 50 N/mm² of copper size
- Mechanical static tensible force: 15N/mm² of copper size



Flessibilità del conduttore
Flessibile classe 5



Senza alogeno
EN 60754-1 & EN 60684-2



Tensione nominale
U₀/U (Um)
3.6 / 6 (7.2) kV



Ritardante la fiamma
EN 60332-1-2



Fuoco ritardante
EN IEC 60332-3-24
(cat C); EN IEC 60332-3-25
(EN50305)



Densità' fumo
EN/IEC 61034-2



Tossicità' gas
EN 50305-9.2



Temperatura Operativa
-50 ... 120 °C

CHARACTERISTICS**Caratteristiche costruttive**

Materiale del conduttore	Rame nudo
Flessibilità del conduttore	Flessibile classe 5
Isolamento	Silicone ad alta temperatura
Senza alogeno	EN 60754-1 & EN 60684-2

Caratteristiche dimensionali

Sezione del conduttore del cavo	120 mm ²
Diametro nominale del conduttore del cavo	14,2 mm
Diametro esterno nominale del cavo	- mm
Diametro esterno min	19,3 mm
Diametro esterno max	22,6 mm
Peso approssimativo del cavo	1247 kg/km

Caratteristiche elettriche

Tensione nominale U ₀ /U (U _m)	3.6 / 6 (7.2) kV
---	------------------

Caratteristiche d'utilizzo

Ritardante la fiamma	EN 60332-1-2
Fuoco ritardante	EN IEC 60332-3-24 (cat C); EN IEC 60332-3-25 (EN50305)
Densità fumo	EN/IEC 61034-2
Tossicità gas	EN 50305-9.2
Temperatura Operativa	-50 ... 120 °C
Temperatura massima di servizio del conduttore	150 °C
Overload maximum core temperature	170 °C
Resistenza chimica	Buona
Fire load	- kWh/m