



Country Ref.: Q102516E200

CONTACT

Market information
 industryprojects.business@lynxgroup.com

PUR control/signal cables for extremely dynamic and drag-chain application, TPU-jacket, shielded, oil resistant, flame retardant, halogen free, UL and CSA approved

STANDARDS

Product UL and CSA approval

Cables designed for continuous moving application, high flexible, oil resistance, halogen free

Applications:

- Tracksystems for tool machines
- Wood machines
- Automatic lines for assembly
- Handling
- Packaging
- Other applications with moderate stresses

CHARACTERISTICS

Construction characteristics

Construction type	(16x0,25)C
Conductor material	Bare copper
Insulation	Polyolefin
Insulation colour	DIN 47100
Taping	Non woven tape
Shielding	≥85% tinned copper braid coverage
Outer sheath	PUR
Sheath colour	Grey RAL 7001
Halogen free	Yes

Dimensional characteristics

Conductor cross-section	0.25 mm ²
Number of cores	16
Outer Diameter	7.5 mm
Copper content	55.1 kg/km



Halogen free
Yes



Operating temp.
-30 ... 80 °C



Storage temperature, range
-40 ... 80 °C



Flame retardant
IEC/EN 60332-1-2; FT1; UL 1581 FT1



Oil resistance
EN 50363-10-2

Dimensional characteristics

Approximate weight 87 kg/km

Electrical characteristics

Rated Voltage U₀/U 300 V

Test voltage 1500 V

Mechanical characteristics

Bending cycles 10 Mio.

Speed 600 m/min

Maximum acceleration 60 m/s²

Usage characteristics

Field of application Dynamic

Operating temperature, range -30 ... 80 °C

Minimum dynamic operating bending radius 6.5 (xD)

Storage temperature, range -40 ... 80 °C

Flame retardant IEC/EN 60332-1-2; FT1; UL 1581 FT1

Oil resistance EN 50363-10-2



Halogen free
Yes



Operating temp.
-30 ... 80 °C



Storage temperature, range
-40 ... 80 °C



Flame retardant
IEC/EN 60332-1-2; FT1; UL 1581 FT1



Oil resistance
EN 50363-10-2