



Country Ref.: Q203406E200

CONTACT

Market information
 industryprojects.business@lynxgroup.com

Controlcables with twisted pairs for data and signal transmission. For extremely dynamic and drag - chain application , shielded, TPU - jacket, oil resistant, flame retardant, halogen free, UL and CSA approved

STANDARDS

Product UL and CSA approval

Cables designed for continuous moving application, high flexible, oil resistance, halogen free

Applications:

- Tracksystems for tool machines
- Wood machines
- Automatic lines for assembly
- Handling
- Packaging
- Other applications with moderate stresses

CHARACTERISTICS

(6x2x0,34)C

Insulation colour	DIN 47100
Taping	Non woven tape
Shielding	85% tinned copper braid coverage
	PUR
Sheath colour	Grey RAL 7001
Halogen free	

	0.34 mm ²
	12
	8.2 mm
Copper content	60.2 kg/km
()	96 kg/km



Halogen free



Operating temp.
 -30 ... 80 °C



Storage temperature, range
 -40 ... 80 °C



IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1



Oil resistance
 EN 50363 - 10 - 2

Rated Voltage Uo/U	300 V 1500 V
Bending cycles	10 Mio.
Speed	600 m/min
Maximum acceleration	60 m/s ²
Field of application	Dynamic
操作度范	- 30 ... 80 °C
Storage temperature, range	- 40 ... 80 °C
Minimum dynamic operating bending radius	6.5 (xD)
	IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1
Oil resistance	EN 50363 - 10 - 2



Halogen free



Operating temp.
- 30 ... 80 °C



Storage temperature, range
- 40 ... 80 °C



IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1
EN 50363 - 10 - 2



Oil resistance
EN 50363 - 10 - 2