



Country Ref.: 71320717

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

Torsion resistant low - voltage cable for free hanging of max. 100 m

STANDARDS

Product EN 50363; HD 22 - 13; IEC 60228; IEC 60502

APPLICATIONS

Low - voltage loop cable WINDLINK LV - RS (N)HXCSLOE was developed for special application condition in wind turbines. The construction is torsion resistant by free hanging of max.100 m. These cables are specified for medium mechanical stress and for operation under permanent influence of sea water and usage outdoor.

Resistance to

- permanent movement
- permanent vibrations
- compressive stress
- oil, EN60811 - 2 - 1, ASTM No.2, 24 h at 100 ° C
- low smoke, IEC 61034, >50 %
- halogen - free IEC 60754
- permanent influence of seawater
- ozone influence, EN 60811 - 2 - 1 clause 8
- suitable for torsion of max. 6 counterclockwise rotations and min. free hanging up from 25 m

Design

Core

Conductor

- Copper, plain, flexible concentrically stranded circular

Insulation

- Extruded halogen - free rubber compound E18 acc. to EN 50363 - 5

Screen

- Tinned wire copper braid, covering min. 80 %

Outer Sheath

- Extruded halogen - free EVA compound EM8 acc. to EN 50363 - 6

CHARACTERISTICS

Conductor flexibility	5
Sheath colour	
Halogen free	IEC 60754 - 2
Overall screen	
With Green/Yellow core	
	2
	6 mm ²
Copper content	- kg/km
Nominal outer diameter	16.0 mm
()	350 kg/km
U ₀ /U (U _m)	0,6/1 kV
	EN 50265 - 2 - 1
Silicone free	Yes
RoHS compliant	Yes
Max. conductor temperature in service	90 °C
Weather resistance	Excellent
Short - circuit max. conductor temperature	250 °C

SELLING AND DELIVERY INFORMATION

Inkjet marking e.g.: WINDLINK LV - RS (N)HXCSLOE 0.6/1 kV | NEXANS I