



Country Ref.: 2PH550

CONTACT

Markets and Products Information
rollingstock.business@lynxeogroup.com

COMMUNICATION CABLES

Lynxéo produces a range of optical fiber cables OM3 (50/125 μm) for onboard communication and data transmission. With its halogen-free cross-linked sheathing material the FLAMEX® optical fiber cables conform to the rolling stock requirements.

STANDARDS

Product EN 45545-2 (HL3); EN 50264-1

DESIGN

1. Patch cord

- . Core: glass OM 3 (diameter = 50μm)
- . Cladding: glass (diameter = 125 ± 3 μm)
- . Coating: acrylate (diameter = 245 ± 10 μm)
- . Buffer: Thermoplastic elastomer (diameter = 900 ± 50 μm)
- . Reinforcement: Aramid yarns
- . Sheath: Cross-linked halogen-free acc. to EN 50264-1 type EM 104 or EM 101 (diameter = 2.00 ± 0.15 mm)

2. Tape(for multi-fibers)

3. Outer sheath

Cross-linked halogen-free acc. to EN 50264-1 type EM 104 or EM101

Example of marking: FLAMEX - Part number - number of fiber x 50/125 - month and year of production

GUIDE TO USE

- Bending radius:
 - Static use: 8 x outer cable diameter
 - For installation and occasional movements: 10 x outer cable diameter



Halogen free
 EN 60754-1 & EN 60684-2



Cable flexibility
 Flexible



Flame retardant
 IEC/EN 60332-1-2



Fire retardant
 EN IEC 60332-3-24 (cat C); EN IEC 60332-3-25 (EN50305)



Smoke density
 EN/IEC 61034-2



Gases toxicity
 EN 50305-9.2



Chemical resistance
 Excellent



Electro magnetic interference resistance
 Yes

CHARACTERISTICS**Construction characteristics**

Fiber optic type	OM3 50/125
Outer sheath	Cross-linked compound
Halogen free	EN 60754-1 & EN 60684-2

Dimensional characteristics

Number of optical fibres	2
Approximate weight	40 kg/km
Outer Diameter	7 mm

Electrical characteristics

Characteristic impedance	- Ohm
--------------------------	-------

Transmission characteristics

Attenuation, nom. 1300 nm (cabled)	1.5 dB/1000m
Attenuation, nom. 850 nm (cabled)	3.5 dB/1000m

Mechanical characteristics

Maximum tensile strength dynamic	250 N/mm ²
Maximum tensile strength static	500 N/mm ²
Cable flexibility	Flexible
Crush resistance (IEC 60794-1-E3)	250 N/cm

Usage characteristics

Flame retardant	IEC/EN 60332-1-2
Fire retardant	EN IEC 60332-3-24 (cat C); EN IEC 60332-3-25 (EN50305)
Smoke density	EN/IEC 61034-2
Gases toxicity	EN 50305-9.2
Chemical resistance	Excellent
Electro magnetic interference resistance	Yes
Minimum dynamic operating bending radius	120.0 mm
Minimum static operating bending radius	60 mm