



Country Ref.: Etude 133056

CONTACT

Market information
industryprojects.business@lynxogroup.com

International Designation:

2 channels 36 AWG coax cable

Cable for invasive monitoring probe

STANDARDS

Product 448-010-3-10; Nexans specification

Characteristics

Very flexible cable with an extremely good mechanical behaviour.
 Withstands miscellaneous sterilisation processes.

CONSTRUCTION

1- CORE (A)

AWG 36 silver plated copper wire.

FEP insulation.

Diameter : 0.32 +/- 0.03 mm

AWG 44 silver plated copper helicoidal screen

Nominal diameter : 0.42 mm

FEP jacket

Diameter : 0.52 +/- 0.03 mm

2 Cores (A) twisted.

Nominal diameter : 1.02 mm

2- SHIELD

AWG 44 silver plated copper helicoidal screen.

Nominal diameter : 1.12 mm

6- JACKET

Suoer Polyamide

Diameter : 1.50 +/- 0.10 mm

Main Characteristics

Minimum bending radius : 5 x Overall diameter.



Cable flexibility
Very flexible



Maximum operating temperature
85 °C



Minimum operating temperature
-30 °C



RoHS compliant
Yes

CHARACTERISTICS**Construction characteristics**

Construction type	Shielded and sheathed
Conductor shape	Single wired
Conductor material	Silver coated copper
Insulation	FEP

Dimensional characteristics

Approximate weight	3.5 g/m
Outer Diameter	1.5 mm

Electrical characteristics

Operating voltage	24 V
-------------------	------

Mechanical characteristics

Cable flexibility	Very flexible
-------------------	---------------

Usage characteristics

Maximum operating temperature	85 °C
Minimum operating temperature	-30 °C
RoHS compliant	Yes