



### CONTACT

Market information  
 industryprojects.business@lynxéogroup.com

**International Designation:** EN 2267-010A 340

**Designed for general Purpose Aircraft Wiring Applications.**

UV Laser printable Wire  
 260°C Operating Temperature Light Weight  
 Arc Tracking Resistant

### STANDARDS

**Product** EN 2267-010

### DESIGN CONSTRUCTION

#### CORE

Stranded Conductor : Nickel Plated High

Strength Copper Alloy (AWG 26 & 24) or  
 Nickel Plated Copper (AWG 22 to 2)

#### INSULATION

Special Polyimide Tape  
 Special UV PTFE Tape(s)

### IDENTIFICATION

#### Standard colour code :

White except AWG 26 which is light yellow and AWG 22 which is light green  
 AWG 24 is available in light blue color (EN2267-010A 002B)

#### Color of marking: green

**Marking text:** EN DR \*\* FR F ++

*DR = Short designation*

*\*\* = AWG Wire Size*

*FR = Country of origin (FR = France)*

*F = Manufacturer (F = Lynxéo)*

*++ = Year of production (i.e. 13 = 2013)*

## CHARACTERISTICS

### Construction characteristics

Colour

S

Conductor material

Nickel-plated copper



Operating temp.  
 -55 ... 260 °C



Oil resistance  
 Very good resistance to aircraft fluids

**Construction characteristics**

Insulating material	Special Polyimide Tape, Special UV PTFE Tape(s)
Type of conductor	Stranded Conductor: Nickel plated alloy

**Dimensional characteristics**

Conductor cross-section (AWG/KCMIL)	2
Maximum core diameter	8.6 mm
minimum core diameter	- mm
Maximum outer diameter	9.16 mm
Minimum cable diameter	8.28 mm
Conductor stranding	37 x 19 x 0.25
Maximum weight	347 g/m
Nominal weight	336.1 g/m

**Electrical characteristics**

Max. DC resistance of the conductor at 20°C	0.61 Ohm/km
Maximal operating frequency	0.002 MHz
Operating Voltage Vo DC	28 V
Operating voltage between phase and neutral	115 V
Operating voltage between phases	200 V

**Usage characteristics**

Operating temperature, range	-55 ... 260 °C
Oil resistance	Very good resistance to aircraft fluids
Arc tracking resistant	Yes



Operating temp.  
-55 ... 260 °C



Oil resistance  
Very good resistance to aircraft fluids